

Deluxe Cord Grips U* R*

Deluxe Cord Grips are woven of stainless steel mesh with an anodized aluminum body for corrosion resistance. They are offered in Single/Double Weave construction to help absorb direct pull, resist flexing and binding, and eliminate strain. Aluminum fittings are offered in a variety of NPT thread sizes. They are recommended for indoor or outdoor use where moisture may be present in the wiring of pendant stations, processing equipment, hand tools, and extension cord sets. They are UL Listed and CSA Certified. Deluxe Cord Grips are suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2. They are also suitable for use in wet locations as long as a listed sealing ring is used between the box and the fitting.

Single/Double Weave

| CAT. NOS. STRAIGHT MALE | 90° MALE | 45° MALE | STRAIGHT FEMALE | CABLE DIA. RANGE (INCHES) | NPT SIZE |
|-------------------------------|----------|----------|--------------------|---------------------------------|-------------|
| L7701 | --- | --- | --- | .187-.250 | |
| L7702 | --- | --- | L7821 | .250-.312 | |
| L7703 | --- | --- | L7822 | .312-.375 | 3/8" |
| L7704 | --- | --- | L7823 | .375-.437 | |
| L7705 | L7761 | L7801 | L7824 | .187-.250 | |
| L7706 | L7762 | L7802 | L7825 | .250-.375 | |
| L7707 | L7763 | L7803 | L7826 | .375-.500 | 1/2" |
| L7708 | L7764 | L7804 | L7827 | .500-.625 | |
| L7709 | --- | --- | --- | .625-.750 | |
| L7711 | L7765 | L7805 | L7828 | .250-.375 | |
| L7712 | L7766 | L7806 | L7829 | .375-.500 | |
| L7700 | L7767 | L7807 | L7831 | .500-.625 | 3/4" |
| L7713 | L7768 | L7808 | L7832 | .625-.750 | |
| L7714 | --- | --- | --- | .750-.875 | |
| L7715 | L7769 | --- | --- | .437-.562 | |
| L7716 | L7771 | L7809 | L7833 | .562-.687 | |
| L7717 | L7772 | L7811 | L7834 | .625-.750 | 1" |
| L7718 | L7773 | L7812 | L7835 | .750-.875 | |
| L7719 | L7774 | L7813 | L7836 | .875-1.000 | |
| L7721 | --- | --- | --- | 1.000-1.125 | |
| L7722 | --- | --- | --- | 1.125-1.250 | |
| L7723 | L7775 | --- | --- | .750-.875 | |
| L7724 | L7776 | --- | --- | .875-1.000 | |
| L7725 | L7777 | L7810 | --- | 1.000-1.125 | 1-1/4" |
| L7726 | L7778 | --- | --- | 1.125-1.250 | |
| L7727 | L7779 | L7820 | --- | 1.250-1.375 | |
| L7728 | L7781 | --- | --- | .750-.875 | |
| L7729 | L7782 | --- | --- | .875-1.000 | |
| L7731 | L7783 | --- | --- | 1.000-1.125 | 1-1/2" |
| L7732 | L7784 | --- | --- | 1.125-1.250 | |
| L7733 | L7785 | --- | --- | 1.250-1.375 | |
| L8011 | --- | --- | --- | 1.312-1.437 | |
| L7770 | --- | --- | --- | 1.437-1.562 | |
| L7750 | --- | --- | --- | 1.562-1.687 | |
| L7760 | --- | --- | --- | 1.687-1.812 | |
| L7780 | --- | --- | --- | 1.750-1.875 | |
| L7734 | L7786 | --- | --- | 1.250-1.375 | |
| L7735 | L7787 | --- | --- | 1.437-1.562 | |
| L7736 | L7788 | --- | --- | 1.500-1.625 | 2" |
| L7737 | L7789 | --- | --- | 1.625-1.750 | |
| L7738 | L7791 | --- | --- | 1.750-1.875 | |
| L8012 | --- | --- | --- | 1.812-1.937 | |
| L8013 | --- | --- | --- | 1.937-2.062 | |
| L7720 | --- | --- | --- | 2.062-2.187 | |
| L7730 | --- | --- | --- | 2.187-2.312 | |
| L7739 | --- | --- | --- | 1.688-1.812 | |
| L7741 | --- | --- | --- | 1.812-1.937 | |
| L7742 | --- | --- | --- | 1.937-2.062 | 2-1/2" |
| L7743 | --- | --- | --- | 2.062-2.187 | |
| L7744 | --- | --- | --- | 2.187-2.312 | |
| L7740 | --- | --- | --- | 2.312-2.437 | |
| L7745 | --- | --- | --- | 1.750-1.875 | |
| L7746 | --- | --- | --- | 1.875-2.000 | |
| L7747 | --- | --- | --- | 2.000-2.125 | |
| L7748 | --- | --- | --- | 2.125-2.250 | |
| L7749 | --- | --- | --- | 2.187-2.312 | 3" |
| L7751 | --- | --- | --- | 2.312-2.437 | |
| L7752 | --- | --- | --- | 2.437-2.625 | |
| L7753 | --- | --- | --- | 2.625-2.812 | |
| L7754 | --- | --- | --- | 2.812-3.000 | |
| L7755 | --- | --- | --- | 3.000-3.250 | |



Straight—Male



90°—Male



45°—Male



Straight—Female

Sold by:



TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 892-2666