

Straight—Male



90°—Male




Straight—Female



90°—Male



Straight—Male



Liquid-Tight Grips U* R*

Liquid-Tight Grips are woven stainless steel mesh with an anodized aluminum body for corrosion-resistance. They are used to connect liquid-tight flexible metal conduit to electrical enclosures to prevent conduit pullout. Each fitting is supplied with an insulated throat to ensure conductor insulation and protect against damage caused by flexing, heat expansion or contraction.

Liquid-Tight Grips are recommended in the wiring of motors and any electrical enclosure where liquid-tight conduit is subject to motion or strain. UL Listed and CSA Certified.

Liquid-Tight Grips

| CAT. NOS. | 90° MALE | 45° MALE | STRAIGHT FEMALE | FITTING SIZE (INCHES) | MESH LENGTH (INCHES) |
|-----------|----------|----------|-----------------|-----------------------|----------------------|
| L7901 | L7915 | L7931 | L7951 | 3/8 | 2-5/8 |
| L7902 | L7916 | L7932 | L7952 | 1/2 | 3-7/8 |
| L7903 | L7917 | L7933 | L7953 | 3/4 | 4-3/8 |
| L7904 | L7918 | L7934 | L7954 | 1 | 5-1/4 |
| L7905 | L7919 | L7935 | | 1-1/4 | 5-5/8 |
| L7906 | L7921 | L7936 | | 1-1/2 | 5-3/4 |
| L7907 | L7922 | L7937 | | 2 | 7-1/2 |
| L7908 | L7923 | L7938 | | 2-1/2 | 9-5/8 |
| L7911 | L7924 | L7939 | | 3 | 10-5/8 |
| L7912 | L7925 | L7941 | | 4 | 12 |

Liquid-Tight Grips for Non-Metallic Type "A" Flexible Conduit

| CAT. NOS. | 90° MALE | FITTING SIZE (INCHES) | MESH LENGTH (INCHES) |
|-----------|----------|-----------------------|----------------------|
| L7961 | L7999 | 3/8 | 9 |
| L7962 | L7990 | 1/2 | 10 |
| L7963 | L7967 | 3/4 | 10-1/2 |
| L7964 | L7968 | 1 | 12 |
| L7965 | L7969 | 1-1/4 | 17 |
| L7966 | L7971 | 1-1/2 | 21-1/2 |
| L7970 | L7972 | 2 | 24 |

Connection Wire Mesh Grips S

Connection Wire Mesh Grips provide additional strain-relief for plugs and connectors used on portable equipment in commercial and institutional applications, and industrial plant and construction site areas which incur abnormally high abuse. Grips are made of galvanized steel.

Connection Wire Mesh Grips

| CAT NO. | CABLE DIA. RANGE (INCHES) | EYE DIMENSIONS (A) (INCHES) | MESH LENGTH (M) (INCHES) |
|---------|---------------------------|-----------------------------|--------------------------|
| L8001 | .30-.43 | 1-11/16 | 4-3/4 |
| L8002 | .40-.56 | 1-11/16 | 6 |
| L8003 | .52-.73 | 1-11/16 | 7 |
| L8004 | .70-.85 | 1-15/16 | 8-1/2 |
| L8005 | .82-1.00 | 1-15/16 | 8-1/2 |
| L8006 | .94-1.25 | 1-15/16 | 10-1/2 |

