

**CPE Products****Telco Products****Wireless Products****OEM Products****International Products**[Company Overview](#)[Reseller](#)[News & Events](#)[Product Spotlight](#)[Service & Support](#)[Contacts](#)[Employment](#)[Search](#)[Home](#)

- [T1 ESF CSU](#)
- [T1 CSU ACE & T1 CSU CP](#)



T1 ESF CSU


The ADTRAN T1 ESF CSU ACE sets the industry standard for size and price versus performance. The unit is available in a compact wallmount package or as a Smart 16 card. This unit is fully compatible with both ANSI T1.403 and AT&T ESF specifications. Easy monitoring and configuration of the T1 ESF CSU ACE is supported through a built-in LCD display and simple menu structure. Access for local and remote configuration is supported through an EIA-232 terminal interface, which also supports T-Watch PRO. For local setup of remote units, the T1 ESF CSU also supports FDL management. The ESF CSU has several features including automatic line build-out to -28 dB for signals received from the network. An automatic equalizer provides DSX-1 signals from 0 to 655 feet toward the DTE. The standalone T1 ESF CSU ACE can be locally powered by a -48 VDC wallmount power supply included with the unit or by a customer-provided -48 VDC power source. The Smart 16 T1 ESF CSU card derives power from the shelf AC or DC source. For central site applications, the Smart 16 shelf can hold 16 T1 ESF CSUs and multiple





_____ for more information on the T1 CSU ACE.

Call ADTRAN Fax Line at (205)963-8200, fax #213



[\[Company Overview\]](#) [\[CPE Products\]](#) [\[Telco Products\]](#) [\[Wireless Products\]](#) [\[OEM Products\]](#) [\[International Products\]](#) [\[Resellers\]](#)
[\[News & Events\]](#) [\[Product Spotlight\]](#) [\[Support & Service\]](#) [\[Contacting Us\]](#) [\[Employment\]](#) [\[Search\]](#) [\[Home\]](#)