Product Specifications



5730 BKBX RG6 60 1000

Material ID: 8202613/10

RG 6 Type 60% Braid Non-Plenum Satellite Coaxial Cable, black jacket, 1000 ft. (305 m) box





CHARACTERISTICS

Construction Materials

Construction Type Non-armored

Center Conductor Material Copper-clad steel wire

Dielectric Material Foam PE
Jacket Material PVC
Shield Braid Coverage 60 %
Shield Braid Gauge 34 AWG
Shield Braid Material Aluminum
Shield/Tape Material Aluminum/Poly

Dimensions

Cable Length 305 m | 1000 ft

Cable Weight 27.00 lb/kft

Diameter Over Center Conductor 1.024 mm | 0.040 in

Diameter Over Dielectric 4.5720 mm | 0.1800 in

Diameter Over Jacket 6.909 mm | 0.272 in

Diameter Over Jacket Tolerance ±0.008 in

Diameter Over Shield/Tape 5.385 mm | 0.212 in Jacket Thickness 0.762 mm | 0.030 in Jacket Thickness, minimum spot 0.610 mm | 0.024 in

Electrical Specifications

Capacitance 53.1 pF/m | 16.2 pF/ft

Characteristic Impedance 75 ohm
Characteristic Impedance Tolerance ±3 ohm

Conductor dc Resistance 28.60 ohms/kft

Dielectric Strength, conductor to shield 3000 Vdc

Jacket Spark Test Voltage 4000 Vac

Nominal Velocity of Propagation (NVP) 82 %

Shield dc Resistance 9.70 ohms/kft

Structural Return Loss 15 dB @ 2200-3000 MHz | 20 dB @ 5-2200 MHz



Product Specifications

5730 BKBX RG6 60 1000 - Material ID: 8202613/10

Structural Return Loss Test Method 100% Swept Tested





Environmental Specifications

Environmental Space Non-plenum

Flame Test Method CM

Safety Standard CETL | ETL UL Temperature Rating 75 °C | 167 °F

General Specifications

Application Satellite
Cable Type Series 6
Jacket Color Black
Product Number 5730
Center Conductor Gauge 18 AWG
Center Conductor Type Solid

Packaging Type CommPak® box

Mechanical Specifications

Minimum Bend Radius, loaded 20 times
Minimum Bend Radius, unloaded 10 times

Performance

Frequency	Attenuation (dB/100 ft)
1 MHz	0.37
10 MHz	0.66
50 MHz	1.41
100 MHz	1.92
200 MHz	2.64
400 MHz	3.73
700 MHz	5.05
900 MHz	5.79
1000 MHz	6.11
1200 MHz	6.73
1450 MHz	7.49
1800 MHz	8.43
2200 MHz	9.35
2500 MHz	9.97
3000 MHz	10.92

Regulatory Compliance/Certifications

AgencyClassificationRoHS 2002/95/ECCompliantISO 9001:2004Compliant



Product Specifications 5730 BKBX RG6 60 1000 - Material ID: 8202613/10





