




13833-001



WA064-CAP

Wireless and
Fiber Ready

Ceiling-Mounted Wireless Enclosure

Ceiling Enclosures create a secure and permanent location for various wireless access points or bridges within drop ceilings. Equipment is supported on the access door. Enclosures are finished in white.

Part Number	Description W x D x L in (mm)	Shipping Weight lb (kg)
13833-001	15.5 x 5 x 16.5 (394 x 127 x 419) Optimized for Cisco® 1250	10 (4.5)
WA064-CAP	10 x 4 x 12.75 (254 x 102 x 324) Optimized for Cisco® Aironet® 350	5 (2.3)



Dome Wireless Enclosure

The AAT-ACE-DOME replaces a single drop ceiling tile to hide wireless access points in open office spaces. The dome is mounted on a fully hinged locking door providing easy access to equipment and cables for authorized technicians only.

- (1) 3/4"H x 3"W (19.1 mm x 80 mm) edge-protected cable access port with approved foam sealing kit
- Includes two sets of standoffs to adjust height of back plate within dome
- Enclosure: 23-3/4"W x 3"D x 23-3/4"L (603.3 mm x 80 mm x 603.3 mm)
- Dome: 6-1/2"H (165 mm), 14" Diameter (360 mm)
- Dome is large enough to accommodate most access points including Cisco's large 1250 series AP
- Product Weight: 10.5 lb (4.76 kg)
- Removable mounting plate is 8 7/8"W x 6-7/8"L (225.43 mm x 174.63 mm)
- Customer must provide (4) 3/8" threaded rods and installation hardware
- Enclosure and dome are finished in white

Part Number	Description W x D x L in (mm)	Shipping Weight lb (kg)
AAT-ACE-DOME	23.75 x 3 x 23.75 (603 x 80 x 603) Domed Wireless Enclosure	21 (9.5)