

Product Cut Sheet

10" DEEP CEILING ENCLOSURE FOR WIRELESS ACCESS POINTS



TELECOMMUNICATION ENCLOSURES

The AAT-CAP is a ceiling mounted enclosure for a wireless access point or bridge. It is designed to be located within drop ceilings and requires a space that is 14-1/2" long by 12" wide and 10" high. It is supported from the drop ceiling "grid" with included brackets and a wire to building structure. Enclosures are painted white to blend with ceiling times.

AAT-CAP has one edge-protected cable access port that includes a fire rated foam sealing kit making it suitable for use in air handling spaces. A fully hinged locking door supports equipment. Several door faceplates are available to match equipment. Blank faceplates are also available. All faceplates include equipment mounting brackets.

■ Cable Entry/Exit

- (1) 3" wide x 3/4" high edge-protected cable access port
- Includes approved fire-rated foam sealing kit

■ Equipment Support

- Removable faceplate, door mounted (ordered separately)

■ Materials

- Enclosure: .060" thick sheet aluminum, riveted construction
- Foam Sealing Kit: Polychloroprene latex compound

■ Packaging

- 1 Enclosure/Carton

■ Approvals

- UL Listed - Communications Circuite Accessory
- UL File Number/E185147 (UL 1863; UL 50; UL 2043)

■ Specifications

- Enclosure: 10-1/5" wide x 13-1/4 long x 10" deep
- Product Weight: 8 lb Enclosure

■ Installation

- Includes installation brackets for 2' ceiling tile grid
- Use approved wire to attach box to building structure



AAT-CAP shown with AAT-CAP 1232 faceplate

Ceiling-Mounted Wireless Access Point Enclosures		
Part Number	Description	Shipping Weight
AAT-CAP	14.5"L x 12"W X 10"D Enclosure (368 mm x 300 mm x 250 mm)	8 lb (3.6 kg)
AAT-CAP-10-P	14.5"L x 12"W X 13"D Enclosure (368 mm x 300 mm x 330 mm) with junction box	9 lb (4.1 kg)
AAT-CAP-S	14.5"L x 12"W X 5"D Enclosure (368 mm x 300 mm x 130 mm)	8 lb (3.6 kg)
Faceplates for Wireless Enclosures		
AAT-CAP-00	Blank (solid) Faceplate	3 lb (1.4 kg)
AAT-CAP-UNI	Universal Faceplate	3 lb (1.4 kg)
AAT-CAP-11*	For Cisco® Aironet® 1100	3 lb (1.4 kg)
AAT-CAP-12	For Cisco® Aironet® 1200	3 lb (1.4 kg)
AAT-CAP-1232	For Cisco® Aironet® 1232	3 lb (1.4 kg)
AAT-CAP-1242	For Cisco® Aironet® 1242	3 lb (1.4 kg)
AAT-CAP Enclosures, 10"D (250 mm) With Faceplates		
AAT-CAP-00-KIT	Blank (Solid) Faceplate	10 lb (4.5 kg)
AAT-CAP-UNI-KIT	Universal Faceplate	10 lb (4.5 kg)
AAT-CAP-11-KIT	For Cisco® Aironet® 1100	10 lb (4.5 kg)
AAT-CAP-12-KIT	For Cisco® Aironet® 1200	10 lb (4.5 kg)
AAT-CAP-1232-KIT	For Cisco® Aironet® 1232	10 lb (4.5 kg)
AAT-CAP-1242-KIT	For Cisco® Aironet® 1242	10 lb (4.5 kg)
AAT-CAP Enclosures, 5"D (130 mm) With Faceplates		
AAT-CAP-S-00-KIT	Blank (Solid) Faceplate	9 lb (4.1 kg)
AAT-CAP-S-UNI-KIT	Universal Faceplate	9 lb (4.1 kg)
AAT-CAP-S-12-KIT	For Cisco® Aironet® 1200	9 lb (4.1 kg)
AAT-CAP-S-1232-KIT	For Cisco® Aironet® 1232	9 lb (4.1 kg)
AAT-CAP-S-1242-KIT	For Cisco® Aironet® 1242	9 lb (4.1 kg)

Note: AAT-CAP 11 may only be used with AAT-CAP.

800-834-4969 U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2011 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, GlobalFrame, Cube-IT Plus, Evolution, OnTrac, and QuadraRack are federally registered trademarks of Chatsworth Products, Inc., Simply Efficient and Velocity are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies.

Rev.3 09/11