



## Wall-Mount Enclosure

The Wall-Mount Enclosure measures 24”H x 42”W x 7.5”D (610 mm x 1070 mm x 191 mm). Includes mounting positions for passive and active equipment, a junction box and a fan to remove heat generated by active components. Mounting positions include space for a single 100 pair 110-style termination block, a single 6-port fiber optic adapter panel, two 2U x 19” spaces for patch panels or other panel mount termination hardware and one 3U x 19” space for active components up to 18”D (460 mm).

The enclosure is pre-punched with knockouts for 1/2” or 1-1/2” electrical conduit for cables and has an insulated, locking, fully-hinged double door to reduce noise and provide security.

- Enclosure is finished in beige

Part Number	Description H x W x D in (mm)	Shipping Weight lb (kg)
AAT-AWM-H	24 x 42 x 7.5 (610 x 1070 x 191)	73 (33.1)



## MUTOA Floor Boxes

Multi-User Telecommunications Outlet Assemblies (MUTOA) are typically small, passive devices that do not rack-mount. CPI’s MUTOA Floor Boxes allow convenient and economical storage of these devices. Available in 24- and 48-port designs.

- Lightweight construction
- Meets TIA-569-B standards



Part Number	Description	Shipping Weight lb (kg)
13701-024	24-Port MUTOA Floor Box	30 (13.6)
13701-048	48-Port MUTOA Floor Box	35 (15.7)