# **Product Information Sheet**

# **BASIC CONSOLIDATION POINT FOR A SINGLE PATCH PANEL (19" X 2U)**



The BCE-48-N is a basic consolidation enclosure designed to be located completely above drop ceilings or completely below raised floors. The enclosure requires a space that is 22" long by 16" wide and 8" deep. BCE-48-N has a removable cover which is secured with six wing nuts. BCE-48-N includes a single pair of threaded equipment mounting rails for 19" wide equipment. Rails are 2U high and pivot to provide easy access to the front and rear of patch panels. Cable tie points are located within the enclosure. Customer must order #12-24 equipment mounting screws and Saf-T-Grip® Cable Management Straps separately.



- One pair of rack-mount rails, 19" wide x 2U high
- Rails pivot to provide access to the front and rear of patch panels

#### ■ Materials

• Enclosure: .060" thick sheet aluminum, riveted construction

# ■ Packaging

• 1 Enclosure/Carton

## ■ Approvals

- UL Listed Communications Circuit Accessory
- UL File Number/E185147 (UL 1863; UL 50; UL 2043)

### ■ Specifications

- Enclosure: 14-3/4" wide x 21-1/4" long x 6-1/2" deep
- Weight: 12 lb

#### ■ Installation

- Customer provides methoad and hardware for ceiling and raised floor attachment.
- Order #12-24 equipment mounting screws separately (P/N 40605-001).
- Saf-T-Grip Cable Management Straps to secure cables (P/N 02008-201).



Part Number	Description	Shipping Weight
BCE-48-N	BCE Enclosure, 19" x 2U, Non-Plenum	12 lb



800-834-4969 US & Canada • www.chatsworth.com

