

# Power Distribution Unit

Corded, non-switched multi-outlet strip



## Model #: PDU1230

- ▶ 14 outlets (2 C19 front / 12 C13 rear)
- ▶ 208/240 volts AC
- ▶ 3 10A and 2 15A circuit breakers
- ▶ L6-30P input plug, 15-ft cord
- ▶ All-metal housing
- ▶ Versatile mounting options including 1U and ZeroU rackmount

## DESCRIPTION

Tripp Lite's PDU1230 offers 208/240V power distribution with L6-30P input plug, 15-foot cord and 14 total output receptacles. Features 2 front-panel C19 outlets, each protected by separate 15A circuit breakers, and 12 rear-panel C13 outlets protected in banks of 4 by 3 separate 10A circuit breakers. Detachable mounting flanges are configurable for wallmount, under-counter or 1U/0U rackmount installation. Uses only 1 rack space (1U) when installed in any 19-inch rack, with the potential for 0U mounting in the cable management area of most rack enclosures. Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes. Attractive housing with 2 front-facing and 12 rear-facing outlets measures only 4.5 inches in depth. Unfiltered electrical pass-through without a power switch makes the PDU1230 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes grounding lug and rugged all-metal case design.

PLUG / OUTLETS: Input: NEMA L6-30P / Output: 2 C19 (front) and 12 C13 (rear)

ELECTRICAL: 208/240V AC, 50/60Hz (Requires NEMA L6-30R wall receptacle)

FORMAT: Supports 19-in. rackmount (1U/0U), wallmount, under-counter and more

## KEY BUYING POINTS

- Corded AC power distribution unit with L6-30P input plug, 2 C19 outlets (front) and 12 C13 outlets (rear)
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19-inch rackmount mounting in both 1U or 0U formats
- Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes, including zero-U rackmount capability in the cable management area or other available space within a rack enclosure
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- Attractive all-metal housing measures only 4.5 inches in depth
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 5 built-in circuit breakers: 2 15A breakers cover 2 C19 outlets; 3 10A breakers cover remaining C13 outlets in banks of 4
- 208V AC, 50/60Hz electrical compatibility

## TYPICAL APPLICATIONS

- Multi-outlet power distribution unit is the ideal means of powering multiple loads in 19-inch rackmount, wallmount and under-counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

## PACKAGE INCLUDES



- PDU1230 Power Strip
- Warranty information
- Instruction manual

## COMPLETE SPECIFICATIONS

<b>SYSTEM OVERVIEW</b>	
<b>System overview:</b>	1U rackmount, 0U vertical rackmount, wallmount or under-counter Power Distribution Unit
<b>Voltage compatibility:</b>	208VAC
<b>Frequency compatibility:</b>	50/60 Hz
<b>OUTPUT</b>	
<b>Output volt amp capacity (VA):</b>	24A
<b>Outlet quantity / type:</b>	14 outlets total - 2 C19 (front), 12 C13 (rear)
<b>INPUT</b>	
<b>Input connection type:</b>	NEMA L6-30P
<b>Input cord length:</b>	15 ft.
<b>Recommended electrical service:</b>	208V 30A line source
<b>PHYSICAL</b>	
<b>Shipping weight (lbs):</b>	5.8
<b>Shipping weight (kg):</b>	2.6
<b>Unit weight (lbs):</b>	5.2
<b>Unit weight (kg):</b>	2.4
<b>Unit Dimensions (HWD/in):</b>	1.75 x 20 x 4.5
<b>Unit Dimensions (HWD/cm):</b>	4.5 x 50.8 x 11.4
<b>Shipping Dimensions (HWD/in):</b>	2.5 x 20.25 x 10
<b>Shipping Dimensions (HWD/cm):</b>	6.3 x 51.4 x 25.4
<b>Material of construction:</b>	Steel
<b>Form factors supported:</b>	1U rackmount, 0U vertical mount, wallmount and under-counter
<b>WARRANTY</b>	
<b>Product warranty:</b>	Lifetime
<b>SPECIAL FEATURES</b>	
<b>TVSS grounding:</b>	Yes, via back panel grounding lug



*The policy of Tripp Lite is one of continuous improvement.  
Specifications are subject to change without notice.  
Therefore, your product may vary slightly from what is currently listed.*



**Tripp Lite World Headquarters**  
1111 W. 35th Street  
Chicago, IL 60609 USA

**Customer Support**  
(773) 869-1234

© 2005 Tripp Lite. All Rights Reserved.

