

PDU12IEC

- ▶ 14 outlets(12 C13, 2 C19)
- ▶ 100-240 volts AC
- ▶ All metal housing
- ▶ Versatile mounting options including 1U and 0U rackmount



DESCRIPTION

Tripp Lite's PDU12IEC AC power distribution unit offers 16 amp capacity in a versatile 100-240 volt, worldwide compatible, multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 1U/0U rackmount installation. Uses only 1 rack space (1U) when installed in any 19 inch rack, with the potential for 0U mounting in the cable management area of most rack enclosures. Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes. Attractive housing with 14 outlets measuring only 4.25 inches in depth. Unfiltered electrical pass-through without a power switch makes PDU12IEC ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 IEC320 C13 and 2 IEC320 C19 outlets, IEC320 C20 inlet connector (user supplies appropriate input cable), set of 16 amp circuit breakers, grounding lug and rugged all-metal case design.

PLUG/OUTLETS - Inlet connection: IEC320 C20/Output: 12 IEC-320 C13 and 2 IEC-320 C19 outlets

ELECTRICAL - 100-240VAC, 50/60Hz, 16A total (User supplies appropriate input cable)

FORMAT - Supports 19 in. rackmount (1U/0U), wallmount, under-counter and more

KEY BUYING POINTS

- Corded AC power distribution unit with 16 amp capacity in a versatile 100-240 volt, worldwide compatible, multi-mount cabinet
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in both 1U or 0U formats
- Detachable flanges with pre-punched access holes and adjustable depth channels allow user configuration in dozens of potential mounting schemes, including zero-U rackmount capability in the cable management area or other available space within a rack enclosure
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- Attractive all-metal housing receptacles measures only 4.25 in. in depth
- 12 IEC320 C13 and 2 IEC320 C19 output receptacles accept common IEC320 C14 and C20 equipment plugs
- IEC320 C20 inlet connection supports a variety of appropriate user-supplied input cords
- Switch-free design prevents the potential for accidental shutoff of connected loads
- 16 amp total electrical capacity with separate 16A circuit breakers
- 100-240V AC, 50/60Hz electrical compatibility

TYPICAL APPLICATIONS

- Multi-outlet power distribution unit is the ideal means of powering multiple loads in 19 inch rackmount, wallmount and under-counter applications: internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.



PACKAGE INCLUDES

- PDU12IEC Rackmount Power Strip
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	1U rackmount, 0U vertical rackmount, wallmount or under-counter Power Distribution Unit, 100-240V compatible
Voltage compatibility:	100-240VAC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	16A (rated)
Outlet quantity / type:	12 IEC-320-C13 and 2 IEC-320-C19 outlets
Outlet orientation:	Back panel: 8 C13, 2 C19. Front panel: 4 C13
Overload protection:	Via 2 built-in 16A circuit breakers
INPUT	
Input connection type:	IEC-320-C20 inlet connection - user supplies input cable (cable selected must have female IEC-320-C19 connection to interface with PDU12IEC inlet)
Input cord length (ft.):	User supplies cord
LEDS ALARMS & SWITCHES	
Switches:	No power switch
PHYSICAL	
Shipping weight (lbs):	3.8
Shipping weight (kg):	1.73
Unit weight (lbs):	3.2
Unit weight (kg):	1.45
Unit Dimensions (HWD/in):	1.75 x 19 x 4.25
Unit Dimensions (HWD/cm):	4.4 x 48.3 x 10.8
Shipping Dimensions (HWD/in):	2.5 x 20.25 x 10
Shipping Dimensions (HWD/cm):	6.35 x 51.4 x 25.4
Material of construction:	Sheet metal
Form factors supported:	1U rackmount, 0U vertical rackmount, wall-mount and undercounter installation supported
Housing color:	Black
Receptacle color:	Black
AC line cord color:	Black
WARRANTY	
Product warranty:	Lifetime
SPECIAL FEATURES	
TVSS grounding:	Back panel nut and bolt grounding lug



*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.

