

DATA SHEET

CISCO IP PHONE 7960G

Cisco IP Communications is a comprehensive system of powerful, enterprise-class solutions enabled by Cisco AVVID, and including IP telephony, unified communications, IP video/audio conferencing, and customer contact applications that help organizations realize business gains by improving operational efficiencies, increasing organizational productivity, and enhancing customer satisfaction. Cisco IP Phones—an integral component of the Cisco IP Communications system—provide unmatched levels of integrated business functionality and converged communications that go beyond today's conventional voice systems.

Figure 1. Cisco IP Phone 7960G



The Cisco IP Phone 7960G, a key offering in the IP Phone portfolio, is a full-featured IP phone primarily for manager and executive needs. It provides six programmable line/feature buttons and four interactive soft keys that guide a user through call features and functions. Audio controls for duplex speakerphone, handset and headset. The Cisco IP Phone 7960G also features a large, pixel-based LCD display. The display provides features such as date and time, calling party name, calling party number, and digits dialed. The graphic capability of the display allows for the inclusion of such features as XML (Extensible Markup Language) and future features.

Figure 2. Cisco IP Phone 7960G



Icon buttons



With Word Overlay, English (Included in documentation package with each phone)

FEATURES


The Cisco 7960G is dynamic and designed to grow with system capabilities. Features will keep pace with new changes via software updates to the phone's flash memory. The phone provides many accessibility methods according to user preference. Various methods or paths include buttons, softkeys, a navigation key, and direct access with the use of corresponding "ghost" digits. Each of the features below will have expanded capabilities in the future:

Messages—



Direct access to voice mail. In the near future voice mail speech to text readout on the display.

Directories—



The Cisco IP Phone 7960G identifies incoming messages and categorizes them for users on the screen. This allows users to quickly and effectively return calls using direct dial-back capability.

The corporate directory integrates with the Lightweight Directory Access Protocol (LDAP3) standard directory.

Settings—



The Settings feature key allows the user to adjust display contrast and select from a large of unique ringer sounds, volume settings for all audio such as ringer, handset, headset, and speaker. Network Configuration preferences can also be set up. (Network configuration is usually set up by the System Administrator.) Configuration can either be automatic or manually set up for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), CallManager, and backup CallManagers.

A huge advantage is the ability for no hands on moves and changes. Just pick up the phone and move to the new location anywhere on your network. No system administration is required.

Services—



The Cisco 7960G allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using extensible markup language (XML) to provide a portal to an ever-growing world of features and information.

Help—



The online help feature gives users information about the phone's keys, buttons, and features. The pixel display allows for greater flexibility of features and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. For example, the Directory button can show local and server-based directory information.

The Cisco IP Phone 7960G features high-quality, speakerphone technology. It also includes an easy-to-use speaker on/off button and microphone mute buttons. These buttons are lit when active.



The internal Cisco two-port Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network via an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. The system administrator can designate separate virtual LANs (VLANs) (802.1Q) for the PC and Cisco IP Phones providing improved security and reliability of voice and data traffic.

A dedicated headset port eliminates the need for a separate amplifier when using a headset. This allows the headset to remain in its cradle, making headset use simpler. The Cisco IP phone's convenient volume control button provides for easy decibel-level adjustments for the speakerphone, handset, headset, and ringer. The handset is ADA and HAC compliant with a maximum handset volume of 13 dB. New 508 capability can be achieved using an in-line headset amplifier such as Walker Equipments W-10 and CE-100 amplifiers.

The dial pad is also ADA compliant.

The footstand of the Cisco 7960G is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The footstand is keyed to match standard wall jack configurations for wall mounting. Two optional wall mount brackets are also offered as noted below.

The Cisco IP Phone 7960G can also receive power down the LAN from any of the new Cisco inline power-capable blades and boxes.

For added security, the audible dual-tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.

Other Cisco IP Phone 7960G features include:

- 24+ user-adjustable ring tones
- A hearing-aid-compatible handset (meets American Disabilities Act [ADA] requirements) and HAC compliance for magnetic coupling to approved HAC hearing aids
- G.711 and G.729a audio compression
- H.323 compatible and Microsoft NetMeeting compatibility
- An IP address assignment—DHCP client or statically configured

- Comfort noise generation and voice activity detection (VAD) programming on a system basis
- EIA/TIA RS-232 port for future add-on options such as line expansion, security access, and more

The phone also includes the following settings:

- Display contrast
- Ring type
- Network configuration
- Call status

SPECIFICATIONS

- Download firmware changes from Cisco CallManager and CCO
- Dimensions: 82 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm) (H x W x D)
- Phone weight: 3.5 lb (1.6 kg)
- Polycarbonate acrylonitrile butadiene styrene (ABS) plastic in textured dark gray color with silver bezel
- 48 VDC required, supplied locally at the desktop using an optional AC to DC power supply (CP-PWR-CUBE-3=)

Also requires ordering one of the AC country cords below.

AC Country Power Cords

CP-PWR-CORD-AP= (Asia Pacific)

CP-PWR-CORD-AR= (Argentina)

CP-PWR-CORD-AU= (Australia)

CP-PWR-CORD-CE= (Central Europe)

CP-PWR-CORD-JP= (Japan)

CP-PWR-CORD-NA= (North America)

CP-PWR-CORD-SW= (Switzerland)

CP-PWR-CORD-UK= (United Kingdom)

Temperature

Operating temperature: 32°F to 104°F (0°C to 40°C)

Relative humidity: 10 percent to 95 percent (noncondensing)

Storage temperature: 14°F to 140°F (-10°C to 60°C)

Certification

Regulatory Compliance

CE Marking

Safety

Underwriters Laboratories (UL) 60950

Canadian Standards Association (CSA) C22.2 No. 60950

Electro-Magnetic Compatibility (EMC)

Federal Communications Commission (FCC) Part 15 (CFR 47) Class B

ICES-003 Class B

EN55022 Class B

CISPR22 Class B

AS/NZ 3548 Class B

VCCI Class B

EN55024

EN 50082-1

EN 61000-3-2

EN 61000-3-3

Telecom

FCC Part 68 (CFR47) hearing aid compatible (HAC)

IC CS-03

ORDERING INFORMATION

Ordering has become too complex to place the order code numbers. Note that “All Cisco IP Phones require the purchase of a phone technology license, regardless of call protocol server attached to.”

Accessories Ordering Information

Optional wall mount kits are available in both locking and non-locking versions:

- CP-LCKNGWALLMOUNT=
- CP-WALLMOUNT-KIT=

Warranty

Cisco IP Phones are covered by a Cisco standard one year replacement warranty.

Optional 14 button add on module CP-7914= provides 14 additional buttons for programming directory numbers (DN) or speed dials or a combination of the 2. Up to two 7914 modules can be used on the 7960.



CISCO IP COMMUNICATIONS SERVICES AND SUPPORT

Cisco IP Communications services and support reduce the cost, time, and complexity associated with implementing a converged network. Cisco and its partners have designed and deployed some of today's largest and most complex IP Communications networks—which means that they understand how to integrate an IP Communications solution into your network.

Cisco design tools and best practices ensure the solution best fits your business needs from the start, eliminating costly redesigns and downtime. Our proven methods ensure a sound implementation that will deliver the functions and features you expect—on time. Support services include remote network operations, network management tools to administer the converged application and network infrastructure, and technical support services.

Through these services, your organization benefits from the experience gained by Cisco and its partners. Leveraging this valuable experience, you can create and maintain a resilient converged network that will meet your business needs today—and in the future.



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus • Czech Republic Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan • Thailand • Turkey • Ukraine United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratm, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0501R)

204179_r_ETMG_SK_1.05

