



# Panel Mounted Devices

47000 & 52000-7M3 Series - For Industrial & Commercial Environments

Sold by:



**10 YEAR LIMITED  
WARRANTY**

## SPECIFICATIONS & FEATURES

### 47000 & 52000-7M3 SERIES

- Provides Seven Mode Protection.
- 47000 Series available in NEMA 1 or 4X enclosure. 52000-7M3 Series comes in a NEMA 12 enclosure with Flush Mount Collar.
- Dry contacts for remote monitoring (NO-C-NC). LED's provide indication of protection status of each mode.
- Design of the 52000-7M3 allows for easy replacement of modules.
- UL 1449 2<sup>nd</sup> Edition Listed

## ENVIRONMENTAL

**STORAGE TEMPERATURE**  
-20°C to 85°C

**OPERATING TEMPERATURE**  
-10°C to 60°C

## STANDARDS & CERTIFICATIONS

**ANSI/IEEE Categories A, B, & C**  
C-62.41 & C-62.45

**UL 1449**  
#E146315

**CSA**  
#LR-94773



DESCRIPTION	WITHOUT SURGE COUNTER	WITH SURGE COUNTER	VOLTAGE RATING 3Ø WYE (4-Wire + Ground)	MODULE NO.
<b>47000 &amp; 57000-7M3 Series</b>				
7-Mode Panel Mount (4 Wired + Ground)	<b>47120-007</b>	—	120/208V AC	—
7-Mode Panel Mount w/ NEMA 4X Enclosure (4 Wire + Ground)	<b>47120-4X7</b>	—	120/208V AC	—
7-Mode Panel Mount (4 Wire + Ground)	<b>47277-007</b>	—	277/480V AC	—
7-Mode Panel Mount w/ NEMA 4X Enclosure (4 Wire + Ground)	<b>47277-4X7</b>	—	277/480V AC	—
7-Mode Panel Mount (4 Wire + Ground)	<b>47347-007</b>	—	347/600V AC	—
7-Mode Modular Panel Mount (4 Wire + Ground)	<b>52120-7M3</b>	<b>52120-7C3</b>	120/208V AC	(3) 120-7M3 (1) 8120-GN
7-Mode Modular Panel Mount (4 Wire + Ground)	<b>52277-7M3</b>	<b>52277-7C3</b>	277/480V AC	(3) 220-7M3 (1) 8120-GN



## Remote Supervisor Provides Clear Indication of Protection Status

All Leviton Panel mounted SPD's are equipped with real-time diagnostics that indicate protection status. However, when these units are mounted in electrical closets, or other out-of-the-way locations, a diagnostic alert might not be seen or heard for some time.

The 52000-RS Remote Supervisor can relay protection failure or power interruption warnings from one or more Leviton panel-mounted SPD's. Warnings are provided by an optically coupled sensor and data lines comprising up to 5000 feet of #20 or #22 twisted-pair wiring. One Remote Supervisor can monitor up to six panel-mounted SPD's. The Remote Supervisor provides both a visual and audible alert, which can be silenced at the press of a button. The unit is equipped with a test circuit, and designed for surface mounting. It draws power from any 120V source through a six-foot line cord.