



**M2000**

- RF & Satellite Field Strength Meter
- Frequency Measurement Range: 25-1550MHz
- Dynamic Range: 45dBmV
- Max Input Voltage: 60dBmV
- Input Sensitivity: 5dBmV
- Input Impedance: 75ohm
- Vertical Led Indicators: 2 rows of 10 (Cable Lo & Cable Hi / Sat1 & Sat2)
- Power Source: 9V Alkaline Battery, Satellite Receiver Voltage
- Power Consumption: Less than 200ma (idle)
- Sleep Mode: 200ua
- Dimensions: 6 1/2"(L) x 3"(W) x 1 1/4"(H)



**1015**

- F connector tool
- Push and seal
- Use with 2133 and 2134 F connectors



**2103**

- F-connector crimp on type for RG59



**1016**

- Coax cutter



**2103-W**

- F-connector crimp on type for RG59, with waterproof O-ring



**1000 RF Kit**

- Kit includes: (4) HS-2's, (3) HS-3's, (4) HS-4's, (5) 2105's, (5) 2126's, (5) 3000-3's, (5) 3000-6's, (5) 3000-10's, (2) 3000-20's, (50) 2101's, (50) 2104's, (25) 2104-QS's, (25) 2102's



**1017**

- Punchdown tool
- 4 pair -110
- Soft rubber handle grip
- Cut blade on one side



**2104**

- F-connector crimp on type for RG6



**1000A RF Kit**

- Kit includes: (4) HS-2's, (3) HS-3's, (4) HS-4's, (1) 1006, (5) 2105's, (5) 2126's, (5) 3000-3's, (5) 3000-6's, (5) 3000-10's, (2) 3000-20's, (25) 2101's, (50) 2133, (25) 2134



**2001 (white)  
2002 (ivory)**

- Wall plate with F connector



**2104-C**

- F-connector for RG6 compression type



**1003**

- F connector tool
- Screwdriver type
- Used to remove/install F-connectors in difficult spaces



**2003**

- Stainless steel BNC wall plate only



**2104-W**

- F-connector crimp on type for RG6, with waterproof O-ring



**1004**

- Coax Stripper
- High quality roller guides
- Self adjusting
- Extra blades available/ 1004-Blade



**2006**

- Stainless dual BNC (wall plate only)



**2104-QS**

- F-connector crimp on type for RG6 quad shield



**1005**

- RF tool & connector kit includes: (1) 1004, (1) 1011, (1) 1003, (100) 2104, (20) 2102, (20) 2101, (2) HS-2, (1) HS-4, (1) 1006



**2009**

- Wallplate RF & Telephone



**2104-QSC**

- F-connector for RG6 quad shield with O-ring
- Compression type



**1011 / 1012 Quad Tool**

- Crimp tool
- For RG58, 59 & 6
- Ratchet type



**2101**

- F-male terminator
- 75 ohm



**2105**

- F-female to BNC-male



**1014**

- Crimp tool for Cat5/Tele/Data
- 7.5" size



**2102**

- Double female F-splice



**2106**

- BNC twist on type RG59