



Refer to wiring diagram on page 7 & 31



6002-FMC-II

Color Flush Mount

- Weather resistant
- Flush or surface mount
- 380 lines of resolution
- Adjustable camera mount
- 0.5 lux @ f1.2 for low light performance
- Available in tinted or clear face plates
- Works with any standard double gang box
- Easy to install

6005-B / 6005-W

Color Waterproof Bullet

- Black or White finish
- Over 380 lines of resolution
- .02 lux sensitivity changes to B&W camera
- 3.6mm lens included
- Power supply included
- Universal swivel mount included
- Miniature size
- Versatile design
- Waterproof

6006

Color Minivision Camera

- 1/4" CCD Image Sensor
- 3.7mm Wide Angle Lens
- 0.5 Lux Low-Light Sensitivity
- Compact Size - 30mm x 30mm
- Power Supply Included
- Includes Mounting Bracket

6007

Color Digital Camera

- Miniature 42.5 mm x 42.5 mm Size
- 2x Digital Zoom
- Over 380 Lines Of Resolution
- 0.05 Lux Sensitivity
- 3.6mm Lens Included
- Auto Trace White Balance
- Universal Swivel Mount Included
- Normal or Mirror Image Viewing Capability
- Power Supply Included

6010

Color Bullet Camera w/Vari-focal Zoom Lens

- 1/3" DSP color Sharp CCD
- 380 lines of resolution
- 0.5 lux at F2.0 (standard)
- 0.1 lux at F2.0 (EX view version)
- 4-9mm vari-focal manual zoom/ F1.6-F2.4
- Weatherproof
- Uses 12VDC power, 90mA regulated

6103 Dome

Color Dome Camera

- 1/3" super sensitive color CCD
- 380 lines of resolution
- 0.2 lux at F2.0
- 3.6mm standard lens
- Lens exchangeable with 5109 lens kit
- Uses 12VDC power, 90mA regulated

5102-FMC-II

Flush Mount Camera

- Weather resistant
- Flush or surface mount
- 420 lines of resolution
- Adjustable camera mount
- 0.1 Lux for low light perf.
- Available in tinted or clear face plates
- Works with any standard double gang box
- Easy to install

5025

B/W Camera with Sony CCD Technology

- 0.6mm lens
- 450 lines High Resolution
- 0.02 lux Sensitivity
- Compact Size - 45mm x 45mm
- Power Supply Included
- Universal Swivel Mount Included
- Dimensions: 1.772" (W) x 1.772" (H)
- Weight: 0.12 kg

5125

IR Night Vision B/W Camera

- Compact appearance
- Power supply DC 12V
- Bracket adjustable for wall or ceiling
- 420 lines of horizontal resolution, 0 lux at F/2.0, 3.6MM board lens
- 1/3-inch CCD approx. 250,920 pixels in EIA and 291,000 in CCIR
- With IR sensitive B/W CCD camera sees in the dark for day and night monitoring up to 30 feet.
- Camera Dimensions: 2-3/8" L x 2" Diameter
- U-Bracket Dimensions: 2-1/8" H x 2-1/8" W

5200

B/W Single Gang Box Camera

- 5006 B&W camera
- Adjustable mount
- Smoked acrylic with white decorative cover
- Includes gasket and power supply
- Fits with standard gang box

