

TAP-INS—SECURELY FASTEN WIRES TO CONCRETE AND OTHER HARD SURFACES



Features

- Route wires along concrete, brick, mortar, cinder blocks and other hard surfaces—without drilling.
- Two specially-hardened drive pins securely fasten wires and prevent cord rotation.
- Install in seconds with only a hammer.
- Integral strain relief grips to hold clips on wire—no need to hold clip while installing it.
- Small, aesthetically pleasing and won't interfere with décor. Clear versions are virtually invisible.
- Weather-proof, ultraviolet (UV) stabilized material protects against deterioration.
- Insulated to protect against shorts during installation / removal.
- Longer pins (LP) are available for soft, porous materials like mortar, cinder block, stucco and wood.

Ordering Information

Designs and specifications are subject to change without notice due to product improvement.

ITW Linx Part Number	Cable Type	Cable Diameter	Color	Pin Length (driven)	Mechanical
<b>TA-1</b> <b>TA-1LP</b>	2 & 3 Pair or ground wire,	0.13"–0.18" 0.13"–0.18"	Clear Clear	0.12" 0.12"	
TA-3*	RG-6 or RG-59	0.25"–0.33"	Clear	0.27"	
<b>TA-5</b>	Quad Shielded RG-11 or 25-pair PBX cable	0.35"–0.40"	Clear	0.33"	
<b>TA-6</b>	Quad Shielded RG-11 or 25-pair PBX cable for corners	0.35"–0.40"	Clear	0.33"	
TA-7*	RG-59	0.20"–0.26"	Black	0.33"	
TA-7HPP*	RG-59	0.20"–0.26"	Black	0.52"	
TA-7HPPC*	RG-59	0.20"–0.26"	Black	0.52"	
TA-8*	Quad Shielded RG-6	0.28"–0.32"	Black	0.33"	
TA-9*	2 and 3-pair	0.11"–0.17"	Black	0.28"	
TA-9LP*	or ground wire	0.11"–0.17"	Black	0.40"	
<b>TA-10</b>	Drop wire	0.28"–0.34"	Clear	0.25"	
TA-11*	RG-59 or RG-6	0.25"–0.31"	Black	0.33"	
TA-11HPP*	RG-59 or RG-6	0.25"–0.31"	Black	0.52"	
<b>TA-12</b>	4-pair	0.15"–0.22"	Clear	0.25"	

\* Non-bold part numbers are special order. Contact factory for pricing and availability.

Applications:

- Concrete
- Brick
- Mortar
- Cinder Blocks
- Aluminum or Vinyl Siding



**CORD CLIPS—SECURELY FASTEN WIRES ALONG ANY SMOOTH SURFACE**









**Features**

- Clips hold securely to any smooth surface, including drywall, plaster, tile walls, wood, metal desks and partitions, plastic, glass and tile.
- Open end clip design allows for repeated installation and removal of cables.
- Four standard sizes hold all conventional voice and data wires, cables and fiber optics.
- Easy-to-Install “press-on” installation.
- Smooth, rounded corners and edges prevent damage to cables, fiber, clothing or installer’s hands.
- All Weather clips are self-adhesive and route cable to any clean, dry, smooth surface.
- Clear clip blends in with substrate material for a virtually invisible installation.



**Ordering Information**

*Designs and specifications are subject to change without notice due to product improvement.*

	<b>ITW Linx Part Number</b>	<b>Cable Type</b>	<b>Cable Diameter</b>	<b>Mechanical</b>
	<b>CC-1-61</b>	2 & 3 Pair Cable, 2 & 3 Pair Modular Cord, 2 Fiber Count Cable	0.16"–0.19"	
	<b>CC-1A-61</b>	RG-59 Coax Cable, 4 Pair to 25 Pair Cable, 2–4 Fiber Count Cable,	0.19"–0.22"	
	<b>CC-2-61</b>	RG-6 Coax Cable, 25 Pair Cable, 2–6 Fiber Count Cable	0.31"–0.49"	
	<b>CC-3-61</b>	50 and 75 Pair Cable, High Count Fiber Cable	0.50"–0.75"	

**Cord Clips**

**Applications:**

- Drywall
- Plaster
- Tile walls
- Wood
- Metal desks & partitions
- Plastic
- Glass and tile.