

CCS-EFX Combination Cabling Section With Extended Fingers

The CCS-EFX is a double-sided vertical cable management trough designed for use with most two- and four-post racks to manage cable at the cross-connect, especially when using angled-face copper patch panels.

The CCS-EFX is manufactured from a combination of strong, lightweight aluminum sheet and plenum-rated composite materials for maximum strength at minimal weight. CCS-EFX is packaged in a single carton for easy handling and includes installation hardware.


- Cable openings on the front are sized to fit 48 patch cords, twice the capacity of the CCS; openings have rounded edges to protect cable and will not deform or break
- Cable openings on front of CCS-EFX align with rack-mount unit on rack allowing cables to exit by rack-mount unit
- The front door hinges open to the right or left and locks in the closed position to protect cables
- Open cabling section on the rear of CCS-EFX allows large premise cable bundles to exit the manager into the rack-mount space. Spin closure latches secure cables
- Attach to 3"D (80 mm) Standard Racks, Universal Racks or QuadraRack
- Mounting hardware and doors are included



Extended fingers of CCS-EFX



Hinged locking door



Usable Depth
Front=8.60" (218.4 mm);
Rear=5.35" (135.9 mm)

Part Number	Height ft (m)	Depth in (mm)	Shipping Weight lb (kg)
6"W (150 mm)			
40098-703	7 (2.1)	14.94 (379.5)	38 (17.2)
40098-705	7.6 (2.3)	14.94 (379.5)	41 (18.6)
40098-715	8 (2.4)	14.94 (379.5)	44 (20.0)
10"W (250 mm)			
40099-703	7 (2.1)	14.94 (379.5)	52 (23.6)
40099-705	7.6 (2.3)	14.94 (379.5)	56 (25.4)
40099-715	8 (2.4)	14.94 (379.5)	60 (27.2)
12"W (300 mm)			
40100-703	7 (2.1)	14.94 (379.5)	56 (25.4)
40100-705	7.6 (2.3)	14.94 (379.5)	60 (27.2)
40100-715	8 (2.4)	14.94 (379.5)	64 (29.0)

Color is black.