



Wall-Mounted, Floor-Supported Cube-iT Plus Cabinet

CUBE-iT Wall-Mounted, Floor-Supported Cabinet Specifications

60"H & 72"H Cabinets (1520 mm & 1830 mm)

- Cabinet body features lockable front door and swing-out rear panel for easy equipment access — cabinet body is supported by an attached wheel base
- For indoor use only, not for use in air-handling spaces
- Usable heights: 60"H (1520 mm) = 33U; 72"H (1830 mm) = 40U
- Wheeled base adds an additional 6" (150 mm) to height
- Includes one pair of 19"W adjustable (front-to-rear), mounting rails with Universal 5/8"-5/8"-1/2" (15.9 mm -15.9 mm -12.7 mm) alternating hole pattern; EIA-310-D Compliant
- Includes cable management space for vertical cable manager accessory
- Cable knockouts include: (4) 1/2" or 3/4", two on top, two on bottom; (10) 2-1/2" or 3", five on top, five on bottom; (5) edge-protection grommets are included for 3" knockouts
- Constructed of riveted and bolted steel with epoxy-polyester hybrid powder coat paint finish; equipment mounting rails and supports are aluminum
- Ships fully assembled with mounting hardware
- Support up to 1000 lb (453.6 kg)

60"H (1520 mm) Cube-iT Plus - Wall Mounted & Floor-Supported					
Part Number & Color		Door Style	Width in (mm)	Depth in (mm)	Shipping Weight lb (kg)
White	Black				
13491-260	13491-760	Metal Door	27.3 (693)	18 (460)	201 (91.2)
13494-260	13494-760	Plexiglass Door	27.3 (693)	18 (460)	192 (87.1)
13492-260	13492-760	Metal Door	27.3 (693)	24 (610)	221 (100.2)
13495-260	13495-760	Plexiglass Door	27.3 (693)	24 (610)	212 (96.2)
13493-260	13493-760	Metal Door	27.3 (693)	30 (760)	246 (111.6)
13496-260	13496-760	Plexiglass Door	27.3 (693)	30 (760)	236 (107.0)
Extra Mounting Rails, 1 pair					
13276-260	13276-760	L-Shaped, Threaded, 33U			12 (5.4)

72"H (1830 mm) Cube-iT Plus - Wall Mounted & Floor-Supported					
Part Number & Color		Door Style	Width in (mm)	Depth in (mm)	Shipping Weight lb (kg)
White	Black				
13491-272	13491-772	Metal Door	27.3 (693)	18 (460)	224 (101.6)
13494-272	13494-772	Plexiglass Door	27.3 (693)	18 (460)	212 (96.2)
13492-272	13492-772	Metal Door	27.3 (693)	24 (610)	247 (112.0)
13495-272	13495-772	Plexiglass Door	27.3 (693)	24 (610)	235 (106.6)
13493-272	13493-772	Metal Door	27.3 (693)	30 (760)	274 (124.3)
13496-272	13496-772	Plexiglass Door	27.3 (693)	30 (760)	262 (118.8)
Extra Mounting Rails, 1 pair					
13276-272	13276-772	L-Shaped, Threaded, 40U			14 (6.4)

Depths for Wall-Mounted, Floor-Supported Cabinet in (mm)			
Cabinet Depth	18 (460)	24 (610)	30 (760)
Cabinet Body Depth	12.2 (310)	18.2 (462)	24.2 (615)
Maximum Usable Depth	16.8 (427)	22.8 (579)	28.8 (732)