

DATA SHEET

## CISCO IP PHONE 7940G

As the market leader in true IP Telephony, Cisco continues to deliver unsurpassed end-to-end data and VoIP solutions, offering the most complete, stylish, fully featured IP Phone portfolio to enterprise and small-to-medium sized customers. Cisco IP phones provide unmatched levels of integrated business functionality and converged communications features beyond today's conventional voice systems.

The Cisco IP phone family includes phones with large pixel-based displays to bring productivity enhancing applications to the phone, as well as customization options that can be modified as needs change, and provide inline power support over Ethernet. The Cisco IP Phone 7940G is multi-protocol enabled supporting Session Initiated Protocol (SIP), Media Gateway Control Protocol (MGCP), as well as Cisco's CallManager Skinny Client Control Protocol (SCCP).


Figure 1. Cisco IP Phone 7940G



The Cisco IP Phone 7940G, a key offering in the IP Phone portfolio, addresses the communication needs of a transaction type worker. It provides two programmable line and feature keys, plus a high quality speakerphone. The Cisco IP Phone 7940G also has four dynamic soft keys that guide users through call features and functions. Built-in headset port and integrated Ethernet Switch are standard with the Cisco IP Phone 7940G. Also includes audio controls for full duplex speakerphone, handset and headset. The Cisco IP Phone 7940G also features a large, pixel-based LCD display. The display provides features such as date and time, calling party name, calling party number, and digits dialed.




## Directories—



The Cisco IP Phone 7940G identifies incoming messages and categorizes them for users on the screen. This allows users to quickly and effectively return calls using direct dial-back capability.

The corporate directory integrates with the Lightweight Directory Access Protocol (LDAP3) standard directory.

## Settings—



The Settings feature key allows the user to adjust display contrast and select from a large number of unique ringer sounds, volume settings for all audio such as ringer, handset, headset, and speaker. Network Configuration preferences can also be set up. (Network configuration is usually set up by the System Administrator.) Configuration can either be automatic or manually set up for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), CallManager, and backup CallManagers.

A huge advantage is the ability for no hands on moves and changes. Just pick up the phone and move to the new location anywhere on your network. No system administration is required.

## Services—



The Cisco 7940G allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using extensible markup language (XML) to provide a portal to an ever-growing world of features and information.

## Help—



The online help feature gives users information about the phone's keys, buttons, and features. The pixel display allows for greater flexibility of features and significantly expands the information viewed when using features such as Services, Information, Messages, and Directory. For example, the Directory button can show local and server-based directory information.

The Cisco IP Phone 7940G features high-quality, speakerphone technology. It also includes an easy-to-use speaker on/off button and microphone mute buttons. These buttons are lit when active.



The internal Cisco two-port Ethernet switch allows for a direct connection to a 10/100BASE-T Ethernet network via an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. The system administrator can designate separate virtual LANs (VLANs) (802.1Q) for the PC and Cisco IP Phones providing improved security and reliability of voice and data traffic.

A dedicated headset port eliminates the need for a separate amplifier when using a headset. This allows the headset to remain in its cradle, making headset use simpler. The Cisco IP phone's convenient volume control button provides for easy decibel-level adjustments for the speakerphone,

handset, headset, and ringer. The handset is Hearing Aid Compatible (HAC) and meets FCC loudness requirements for Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers.

The dial pad is also ADA compliant.

The footstand of the Cisco 7940G is adjustable from flat to 60 degrees to provide optimum display viewing and comfortable use of all buttons and keys. The footstand is keyed to match standard wall jack configurations for wall mounting. Two optional wall mount brackets are also offered as noted below.

The Cisco IP Phone 7940G can also receive power down the LAN from any of the Cisco inline power-capable blades and boxes.

For added security, the audible dual-tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.

Other Cisco IP Phone 7940G features include:

- 24+ user-adjustable ring tones
- A hearing-aid-compatible handset (meets American Disabilities Act [ADA] requirements) and HAC compliance for magnetic coupling to approved HAC hearing aids
- G.711 and G.729a audio compression
- H.323 compatible and Microsoft NetMeeting compatibility
- An IP address assignment—DHCP client or statically configured
- Comfort noise generation and voice activity detection (VAD) programming on a system basis

The phone also includes the following settings:

- Display contrast
- Ring type
- Network configuration
- Call status

## **SPECIFICATIONS**

- Download firmware changes from Cisco CallManager and CCO
- Dimensions: 8 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm) (H x W x D)
- Phone weight: 3.5 lb (1.6 kg)
- Polycarbonate acrylonitrile butadiene styrene (PABS) plastic in textured dark gray color with silver bezel
- 48 VDC required, supplied locally at the desktop using an optional AC to DC power supply (CP-PWR-CUBE-3=)

Also requires ordering one of the AC country cords below.

### **AC Country Power Cords**

CP-PWR-CORD-AP= (Asia Pacific)

CP-PWR-CORD-AR= (Argentina)

CP-PWR-CORD-AU= (Australia)

CP-PWR-CORD-CE= (Central Europe)

CP-PWR-CORD-JP= (Japan)



CP-PWR-CORD-NA= (North America)

CP-PWR-CORD-SW= (Switzerland)

CP-PWR-CORD-UK= (United Kingdom)

## **Temperature**

Operating temperature: 32°F to 104°F (0°C to 40°C)

Relative humidity: 10 percent to 95 percent (noncondensing)

Storage temperature: 14°F to 140°F (–10°C to 60°C)

## **Certification**

### **Regulatory Compliance**

CE Marking

### **Safety**

Underwriters Laboratories (UL) 60950

Canadian Standards Association (CSA) C22.2 No. 60950

### **Electro-Magnetic Compatibility (EMC)**

Federal Communications Commission (FCC) Part 15 (CFR 47) Class B

ICES-003 Class B

EN55022 Class B

CISPR22 Class B

AS/NZ 3548 Class B

VCCI Class B

EN55024

EN 50082-1

EN 61000-3-2

EN 61000-3-3

### **Telecom**

FCC Part 68 (CFR47) hearing aid compatible (HAC)

IC CS-03

## **ORDERING INFORMATION**

Ordering has become to complex to place the order code numbers. Note that “All Cisco IP Phones require the purchase of a phone technology license, regardless of the call protocol server phone is attached to.”

### **Accessories Ordering Information**

Optional wall mount kits are available in both locking and non-locking versions:

- CP-LCKNGWALLMOUNT=
- CP-WALLMOUNT-KIT=

### **Warranty**

Cisco IP Phones are covered by a Cisco standard one year replacement warranty.

## **CISCO IP COMMUNICATIONS SERVICES AND SUPPORT**

Cisco IP Communications services and support reduce the cost, time, and complexity associated with implementing a converged network. Cisco and its partners have designed and deployed some of today’s largest and most complex IP Communications networks—which means that they understand how to integrate an IP Communications solution into your network.

Cisco design tools and best practices ensure the solution best fits your business needs from the start, eliminating costly redesigns and downtime. Our proven methods ensure a sound implementation that will deliver the functions and features you expect—on time. Support services include remote network operations, network management tools to administer the converged application and network infrastructure, and technical support services.

Through these services, your organization benefits from the experience gained by Cisco and its partners. Leveraging this valuable experience, you can create and maintain a resilient converged network that will meet your business needs today—and in the future.



#### Corporate Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

#### European Headquarters

Cisco Systems International  
BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

#### Americas Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

#### Asia Pacific Headquarters

Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus  
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland  
Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland  
Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden  
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratum, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0501R)  
204179.q\_ETMG\_SK\_1.05