



M-Series MegaFrame® Cabinet 72", 78" and 84" (1830 mm, 1980 mm and 2130 mm)

The M-Series MegaFrame[®] Cabinet System supports a vast array of potential applications. The cabinet is available in a variety of heights, widths and depths to meet the most stringent demands. Also, the M-Series Cabinet System allows the user to select mounting rails to accommodate today's variety of rack-mount equipment.

Specifications:

- \bullet Available in three heights; 72", 78" and 84" (1830 mm, 1980 mm and 2130 mm)*
- Available in 19" or 23" EIA standard rack widths
- Available in four depths; 24", 30", 36" and 39" (610 mm, 760 mm, 910 mm and 990 mm)
- Available with or without top or side panels
- Side panels are easy-to-remove and locking
- Can be ordered with or without doors in a variety of materials and styles
- Cabinet is available with a choice of tapped 12-24, square-punched, Sun^{\circledast} or IBM^{\circledast} rails
- Rack-mount unit marks simplify equipment installation
- Hardware for each rail type is included
- All vertical mounting rails are available in half heights (also sold separately)
- Manufactured from aluminum custom designed for maximum strength and functionality
- Bolted construction, delivers fully or partially assembled
- Load Rating: 2000 lb (907.2 kg)
- UL Listed: File E212094; Category DUXR (US) Communications Circuit Accessory

Cabinet Includes:

- (1) Four-Post Frame (anodized aluminum finish)
- (4) Vertical Mounting Rails & Mounting Hardware
- (2) Locking, Easy-To-Remove Side Panels
- (1) "Quick-Release" Front Door
- (1) "Quick-Release" Rear Door
- (1) Vented Top Panel & Six Cable Access Ports
- (2) Vertical Half Height Cable Managers (wide)
- (4) Leveling Feet
- (1) PDU Mounting Bracket Kit
- (1) Multi-Bay Attachment Hardware Kit
- (4) Floor Anchor Clamps
- (1) Bag of 50 Each #12-24 Rack Channel Mounting Screws with tapped rails
- (1) Bag of 16 each M6 Cage Nuts and Screws, and 25 each #12-24 Cage Nuts and Screws with square-punched rails

*Note: Special 8' (2.4 m) cabinets are available in standard lead times.

MegaFrame® Cabinet System 72", 78" and 84" (1830 mm, 1980 mm and 2130 mm)

Dimensions:

Height Dimensions - in (mm)				
All Cabinet Styles	72 (1830)	78 (1980)	84 (2130)	
Usable Vertical Panel Space	38U, 66.50 (1689.1)	42U, 73.50 (1866.9)	45U, 78.75 (2000.3)	
Overall Height without Leveling Feet	72.02 (1829.3)	78.02 (1981.7)	84.02 (2130.0)	
Overall Height with Leveling Feet	72.92 (1852.2)	78.92 (2004.6)	84.92 (2157.0)	
Overall Height with Casters	75.70 (1922.8)	81.70 (2075.2)	87.70 (2230.0)	
Frame Vertical Opening	67.90 (1724.7)	73.90 (1877.1)	79.90 (2029.5)	

Width Dimensions - in (mm)				
Usable Equipment Panel Width	19″ EIA	23″ EIA		
Overall Width	27.32 (693.9)	31.32 (795.5)		
Frame Horizontal Opening	20.20 (513.1)	24.20 (614.7)		

Depth Dimension Cabinet Only (With Doors) - in (mm)				
Nominal Cabinet Depth	24 (61)	30 (760)	36 (910)	39 (990)
Maximum Mounting Depth - Rail to Rail	24.00 (609.6)	30.00 (762.0)	36.00 (914.4)	39.00 (990.6)
Overall Depth - Inside Door to Inside Door	27.22 (691.4)	33.22 (843.8)	39.22 (996.2)	42.22 (1072.4)
Overall Depth - Door Face to Door Face	27.62 (701.5)	33.62 (853.9)	39.62 (1006.3)	42.62 (1082.5)


Depth Dimension Frame Only (Without Doors) - in (mm)				
Nominal Cabinet Depth	24 (610)	30 (760)	36 (910)	39 (990)
Maximum Mounting Depth - Rail to Rail	24.00 (609.6)	30.00 (762.0)	36.00 (914.4)	39.00 (990.6)
Overall Depth	26.13 (663.7)	32.13 (816.1)	38.13 (968.5)	41.13 (1044.7)

Shipping Weights - Ib (kg)				
All Cabinet Styles - in (mm)	72 (1830)	78 (1980)	84 (2130)	
Minimum	152 (68.9)	152 (68.9)	155 (70.3)	
Maximum	251 (113.9)	262 (118.8)	287 (130.2)	

Part Number Configurator

When ordering an **M-Series Cabinet**, the part number is always preceded by the letter **M**. Use the part number matirx below to configure your M-Series Cabinet. Choose the **W**idth, **H**eight, **D**epth, Cabinet **S**tyle, **C**olor, **D**oor, and Shipping **O**ption.

Example Cabinet Part Number: M1221-112



Notes:

1. Frame only style cannot be ordered with doors

2. Server rail styles are only available on cabinets 36" (910 mm) or 39" (990 mm) in depth.

3. Color refers to mounting rails and side panels and metal/perforated metal door panels. Frame is silver-colored anodized aluminum. For further assistance call 800-834-4969.

M-SERIES MEGAFRAME® CABINET



48" (1220 mm) M-Series MegaFrame® Cabinet

The 48"H (1220 mm) M-Series MegaFrame® Cabinet is designed for space conscious customers who demand value. The cabinet is available in a variety of widths and depths. Multiple cabinets can be mounted side-by-side using optional baying hardware. The cabinet is available in white, black or gray powder-coated finish. The cabinet is also available in a frame only configuration.

Note: When ordering a frame only configuration, the mounting rails have a powder-coated finish based on your color selection. The frame is always silvercolored anodized aluminum.


Specifications:

- Provides 25U of rack-mount space
- Available in 19" EIA or 23" EIA standard rack widths
- Available in three depths; 24", 30" and 36" (610 mm, 760 mm and 910 mm)
- Load Rating: 2000 lb (907.2 kg)

When ordering an **M-Series Cabinet**, the part number is always preceded by the letter **M**. Use the part number matirx below to configure your M-Series Cabinet. Choose the Width, Height, Depth, Cabinet Style, Color, Door, and Shipping Option.

Example Cabinet Part Number: M2530-112

Part Number Configurator



2-46

Notes:

1. Frame only style cannot be ordered with doors

2. Color refers to mounting rails and side panels and metal/perforated metal door panels. Frame is silver-colored anodized aluminum. For further assistance call 800-834-4969.

> I TWAcommecom http://www.TWAcomm.com Toll Free: (877) 389-0000

Sold by



Frame Only Style