


# 2x2 and 4x4 FIBER-DUCT™ Routing System

Sold by:





## specifications

The 2x2 and 4x4 routing systems shall be used to route, segregate and protect fiber optic and communication cabling. The solid wall routing systems should be UL Listed as an optical fiber channel for general-purpose use. They shall be compliant with UL2024A and NEC articles 770 and 800 when installed per instructions. The slotted wall channel and cover shall be UL Recognized. A full complement of fittings with a 2" minimum bend radius, snap-on covers and mounting brackets shall be available. Channel and fittings shall be manufactured from impact-resistant and flame retardant (V-0) materials. Channel shall have non-slip snap-on covers that can be easily removed to allow access for moves, additions and changes. Channel and fittings finish shall be pure color, resist scratches, dents, and not peel or corrode. Available system colors shall be yellow, orange and black. A full complement of brackets shall be available for attaching system components to ladder rack, threaded rod, auxiliary framing, strut, equipment racks, and raised floor pedestals.



## technical information



Dimensions are in inches (Dimensions in parentheses are metric)

Open channel 50% fill capacity (2" pile up):		
2x2 FIBER-DUCT™ System	Cable	No. of Cables
	1.6mm	561
	2.0mm	357
	3.0mm	160
	CAT6 5.2mm	53
	CAT5e 5.5mm	47
4x4 FIBER-DUCT™ System	1.6mm	1219
	2.0mm	775
	3.0mm	347
	CAT6 5.2mm	115
	CAT5e 5.5mm	103
<b>Material:</b> Rigid PVC (channel), ABS (fittings)		
<b>Flammability:</b> 94V-0		
<b>Approvals:</b> UL Listed (File No. E236504) solid wall UL Recognized (File No. E147128) slotted wall CSA Certified (File No. 016446 0 000) slotted wall		
<b>CSI spec form:</b> LP-CSISPEC-FD-1		

## key features and benefits

<b>Large capacity 2" x 2" and 4" x 4" sizes</b>	Ideal for routing, segregating, and protecting large amounts of fiber cabling; provides a more secure installation for fiber or high performance copper cabling
<b>Minimum 2" bend radius control fittings</b>	Bend radius control in fittings helps prevent excessive bends in fiber optic and high performance copper cabling
<b>Snap-on covers</b>	Covers snap on or off channel and fittings to enclose or gain access to system; fully encloses the channel to provide protection per UL2024A; provides quick and easy access for moves, adds and changes
<b>Mates to PANDUIT® Cable Management Rack Panels</b>	Provides methods to mate system to equipment mounted on standard EIA 19" or 23" equipment racks and vertical cable managers

## applications

The FIBER-DUCT™ 2x2 and 4x4 Routing Systems are comprised of channel, fittings and brackets designed to segregate, route and protect fiber optic cable and copper cabling. It is suited for data center applications where cable is routed from distribution areas to equipment cabinets or racks. It is used in Telco Central Offices to route fiber optic jumper cables between fiber distribution frames and equipment bays. It can be deployed over the racks or in approved under floor applications. Fittings maintain a minimum 2" bend radius to protect against signal loss due

to excessive cable bends. Available system colors are yellow, orange and black to differentiate various types of cabling. A full complement of brackets is available to attach system components to support structures found in all applications.

The FIBER-DUCT™ 2x2 and 4x4 Routing Systems are part of the PANDUIT® complete fiber distribution system, which includes the FIBERRUNNER™ 12x4, 6x4, 4x4 and 2x2 Routing Systems and OPTICOM™ HD Cable Management products.

### Channel & Cover

2x2 solid wall channel (6 ft):	S2X2**6NM
4x4 solid wall channel (6 ft):	S4X4**6NM
2x2 slotted wall channel (6 ft):	E2X2**6
4x4 slotted wall channel (6 ft):	E4X4**6
2x2 cover (6 ft):	C2**6
4x4 cover (6 ft):	C4**6

### Fittings

2x2 coupler:	FCF2X2**
4x4 coupler:	FCF4X4**
2x2 horizontal right angle:	FRA2X2**
4x4 horizontal right angle:	FRA4X4**
2x2 horizontal tee:	FT2X2**
4x4 horizontal tee:	FT4X4**
2x2 four way cross:	FFWC2X2**
4x4 four way cross:	FFWC4X4**
2x2 end cap:	FEC2X2**
4x4 end cap:	FEC4X4**
2x2 vertical tee:	FVTHD2X2**
4x4 vertical tee:	FVT4X4**
1-port spillout to 1.5" I.D. corrugated tubing:	FIDT2X2**
2-port spillout to 1.5" I.D. corrugated tubing:	FIDT4X4BL
3-sided vertical tee trumpet spillout:	FTR4X4**
3-sided BRC trumpet spillout for 2x2 exit:	FTR2X2**
2x2 inside vertical 45°:	FIV452X2**
4x4 inside vertical 45°:	FIV454X4**
2x2 outside vertical 45°:	FOV452X2**
4x4 outside vertical 45°:	FOV454X4**
2x2 inside vertical right angle:	FIVRA2X2**
4x4 inside vertical right angle:	FIVRA4X4**
2x2 outside vertical right angle:	FOVRA2X2**
4x4 outside vertical right angle:	FOVRA4X4**
4x4 to 2x2 FIBER-DUCT™ Reducer:	FRF42**
4x4 FIBER-DUCT™ System to 4x5 standard vertical slotted duct fitting:	FRF4544BL
2x2 bend radius control trumpet:	TRC2BL
4x4 bend radius control trumpet:	TRC4BL
2x2 innerduct transition:	FITF2X2
4x4 innerduct transition:	FITF4X4A
4x4 innerduct transition:	FITF4X4B
4x4 adapter to ADC 4x4 FiberGuide™:	FADC4X4
4x4 adapter to various 4x4 systems:	FTDNS4X4**
2x2 plastic snap rivet:	NR2WH
4x4 plastic snap rivet:	NR4BL
Plastic bolts and wing nuts:	F14PWN
Plastic bolts and hex nuts:	F14PN
2x2 boltless snap bracket:	FBB2
4x4 boltless snap bracket:	FBB4

### Mounting Brackets

Existing 1/2" thr rod brkt:	FTRBE12
Existing 5/8" thr rod brkt:	FTRBE58
New 1/2" thr rod brkt:	FTRBN12
New 5/8" thr rod brkt:	FTRBN58
Under-floor brkt:	FUSB
1/2" thr rod to 1 1/2" ladder rack brkt:	FLB12X15
5/8" thr rod to 1 1/2" ladder rack brkt:	FLB58X15
1/2" thr rod to 2" ladder rack brkt:	FLB12X20
5/8" thr rod to 2" ladder rack brkt:	FLB58X20
2 pc. ladder rack 1/2" thr rod:	F2PCLB12
2 pc. ladder rack 5/8" thr rod:	F2PCLB58
Ladder rack brkt:	FLRB
"L" wall mount brkt:	FLB
Strut mt l frm brkt 1/2" thr rod:	FTRB12
Strut mt l frm brkt 5/8" thr rod:	FTRB58
Adjustable "Z" bracket:	FZBA1.5X4
Top rail of rack support bracket:	FMRB
EIA/TIA threaded rod mounting bracket:	FEIAB58

\*ADC's 6x4 FiberGuide Management Systems is a registered trademark of ADC Telecommunications, Inc.

\*\* Substitute: YL=Yellow OR=Orange BL=Black