

# SurgeGate Series AC Protection



AC Protection

SurgeGate

## M4KSU—PREMIER SERIES 4-OUTLET AC SURGEGATE



### Features

- AC protection for telecom systems
- SurgeGate Plus Circuitry
- Expandable protection using SurgeGate Modules
- Four switched AC power outlets
- Diagnostic indicator lights (four)
- Eight foot power cord with right angle plug
- EMI/RFI noise filtration
- Mounting brackets included
- **AVAYA** approved product: 145J, 700209794

### Technical Specifications

*Designs and specifications are subject to change without notice due to product improvement.*

#### PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	4
Grounding Requirements	Uses Electrical AC Ground
Ground Impedance	N/A
Width	4.25"
Height	9.5"
Depth	1.5"
Weight	2.0 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	Up to \$50,000



For up-to-date warranty information see our web site: [www.itwlinx.com](http://www.itwlinx.com)



#### SIGNAL LINE SURGE PROTECTION:

##### TELCO CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Clamping Level	N/A
Response Time	N/A
Capacitance	N/A
Suppression Modes	N/A
Wires Protected	N/A
Termination Type	N/A

##### COAX CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Response Time	N/A
Termination	N/A
Antenna/Cable Lines Protected	N/A
Antenna/Cable Clamping Level	N/A
Antenna/Cable Attenuation	N/A
Satellite Lines Protected	N/A
Satellite Clamping Level	N/A
Satellite Attenuation	N/A

##### LAN CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Performance Rating	N/A
Clamping Level	N/A
Response Time	N/A
Wires Protected	N/A
Termination Type	N/A

#### AC SURGE PROTECTION:

SurgeGate Plus Circuitry	Yes
Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Over/Undervoltage Voltage Protection	Yes
Overvoltage Voltage Shutoff	147V ±8V
Undervoltage Voltage Shutoff	87V ±8V
Single Pulse Energy Dissipation	1650 Joules
Peak Impulse Current	52,000 A
EMI/RFI Noise Filtration	50db (99.7%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level	200V Peak, 141 Rms
UL 1449 Rating	330V
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Right Angle
Number of Outlets	4
Switched Outlets	4
Cord Length	8'



**More information is available in the Technical Reference section of this catalog, turn to page 86.**

#### Applications:

- Telephone Systems
- Workstations
- Printers
- Fax Machines
- Copiers
- TVs / VCRs
- Cameras
- Access Controls
- Alarms

### Ordering Information

ITW Linx Part Number	Description
M4KSU-60	4-outlet AC surge protector, with SurgeGate Plus circuitry and modular mounting capabilities.