

Features

Station Capacity
 Single Exchange:
 4 Master Stations
 64 Substations

Up to 16 Exchanges: 64 Master Stations 1024 Substations

System Integration
 Remote control and monitoring via RS-232
 communication protocol

System Management
 PC programming and monitoring software
 Program and maintain entire system via off- or on-site PC

Audio Recording
 Recording capability from the master or telephone through the
 audio recording output

Data Logging
 The operating log of all control functions can be stored on PC for future reference

Master Station Flexibility
 Aiphone master station with alphanumeric display and clock line communication

Paging Interface
 For external amplifier zone distribution with 16 control ports

External Audio Input For station and external amplifier zone distribution with four trigger inputs

Functions

- Telephone
 Direct-in dial
 Outside line access
 Manual forwarding
 Off-site forwarding
- Call Forwarding Manual Remote (Call Capture)
 Time-based
 No answer
 Busy
 Off-site telephone
- Paging
 Zone (19)
 All-zone paging
 Public Address (16)
- Scan Monitor
- Master Station Grouping (16)
- Emergency Conference
- Auto-Dial and Redial
- · Call Transfer/Hold
- Priority (Emergency/Normal)
- Automatic Time-out
- Call Queuing
- Selective Response



For ideas, specifications

toll-free at 800-692-0200.

System Integration

and assistance call an

Aiphone Technician,

