



EX-Strobe

Catalog Number Logic

EX **M** **1** **R** - **G** - **B2**
 (1) (2) (3) (4) (5) (6)

(1) Series - "EX"

Explosion proof Xenon strobe fixture.

(2) Flashboard - Lamp Type (Xenon)

M - Medium intensity 2 million candlepower
 (flash rate 60 FPM)

(3) Voltage / Frequency

- 1 - 120 Volt AC, 50 / 60 Hz.
- 2 - 240 Volt AC, 50 / 60 Hz.
- 8 - 10 to 30 Volt DC
- 9 - 90 to 130 Volt DC

(4) Inner Fresnal Lens - Color

- A** - Amber
- B** - Blue
- C** - Clear
- G** - Green
- R** - Red

(5) Guard

G - Cast guard
 (omit "G" if guard not required)

(6) Mounting Style

- B2** - 3/4" npt. wall mount
- C2** - 3/4" npt. ceiling mount
- P2** - 3/4" npt. pendant mount
- S4** - 1 1/4" npt. stanchion mount





(7) Special Options

SR- Sealing ring for inverted mounting.
 (must be used for globe up position to maintain
 Type 3R enclosure / wet location listing)

Note: Lamp is included.

**Consult factory for any catalog number or options
 not listed above for price and availability.**

Ordering Guide

Lamp Type	Voltage	Hub Size	Pendant Mount	Ceiling Mount	Wall Mount	Hub Size	Stanchion Mount
							
Medium Intensity	120 V AC	3/4"	EXM 1R - G - P2	EXM 1R - G - C2	EXM 1R - G - B2	1 1/4"	EXM 1R - G - S4
	240 V AC	3/4"	EXM 2R - G - P2	EXM 2R - G - C2	EXM 2R - G - B2	1 1/4"	EXM 2R - G - S4
2 million candlepower	10-30 V DC	3/4"	EXM 8R - G - P2	EXM 8R - G - C2	EXM 8R - G - B2	1 1/4"	EXM 8R - G - S4
	90-130 V DC	3/4"	EXM 9R - G - P2	EXM 9R - G - C2	EXM 9R - G - B2	1 1/4"	EXM 9R - G - S4

Ordering Notes:

1. All catalog numbers shown are with red inner fresnal lens (see Catalog Number Logic for alternate colors).
2. All fixtures are shown with guard. To order fixture without guard, remove "G".