

WIDE BAND AMPLIFIERS

WBA125F & WBA425F 1 & 4-Way Wide Band Amplifiers

Satellite USA amplifiers can be used as a solution for long cable runs throughout an installation. The new wide band amplifiers are only available in a four input / four output model and a single input model that will provide amplification to compensate for runs up to 250 feet of RG6 coaxial cable. They can be used before or after a multiswitch and are either line powered or through a remote power supply.

FREQUENCY RANGES	
WBA425F	250 ... 2200 MHz
WBA125F	250 ... 2200 MHz
GAIN	
WBA425F & WBA125F	10 dB @ 250 MHz
	16 dB @ 950 MHz
	25 dB @ 2200 MHz

ISOLATION	
WBA425F	>26 dB
WBA125F	>26 dB
MAX OUTPUT LEVELS	
WBA425F	+3.25 dBm
WBA125F	+3.25 dBm
MAX INPUT LEVELS	
WBA425F	-21.75 dBm
WBA125F	-21.75 dBm



WBA125F



WBA425F

 **Lead Free**
Made in Germany

325 LOC CANOE CIRCLE
STEVENSVILLE, MD 21666
TEL:410.643.6535

WEB:WWW.SATELLITEUSA/ELECTRONICS.COM