

Series II, two-port Category 5e, T568B, 45° - OR-60950053

Series II, two-port Category 5e, T568B, 45°



FEATURES

- Angled module design
- TIA/EIA Category 5e performance
- Linear 110 paired punch down
- Front removable
- Rugged snap-in design
- Icon compatible

BENEFITS

- Protects cord connections
- Ensures installed link and channel performance
- Faster than other termination methods
- Less intrusive access for adds, moves, changes
- Quick and easy

- Supports TIA/EIA 606 standard

Specifications

CONSTRUCTION INFO

Component4:	Printed circuit board
Material3:	Phosphor bronze
Finish Plating3:	Nickel plating and tin lead over plate
Material2:	Phosphor bronze
Component1:	Plastic Series II Housing
Component2:	Array of eight linear modular contacts
Material1:	High Impact Thermoplastic ABS 94V-0
Component3:	IDC contacts, 110 D4
Material4:	Two-sided FR-4 epoxy resin/glass base with solder mask
Finish Plating2:	Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

DIMENSION INFO

Width U S:	1.90"
Depth Metric:	39.62 mm
Width Combined:	1.90" (48.26 mm)
Height Combined:	.92" (23.37 mm)
Depth U S:	1.56"
Depth Combined:	1.56" (39.62 mm)
Height Metric:	23.37 mm
Width Metric:	48.26 mm
Height U S:	.92"

GENERAL INFO

Category Performance Application:	Category 5e/UTP
Product Type Accessory:	Modular Jack
Number Of Ports:	2-port
Critical Size:	1 unit
Product Type Accessory For Filter:	Modular Jack
Color Filter:	Fog White
Footprint:	Series II

TECHNICAL INFO

Wire Gauge:	22-26 AWG
Category Rating:	Category 5e