



Outdoor housing for SNC-RX550N; SNC-RZ25N



SNC-RX550N

NORMAL HOUSING

UNI-ONL7C2 (clear lower dome)
UNI-ONL7T2 (tinted lower dome)

- Outdoor dome, UV protected
- Thermostatically controlled heater
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate lower dome
- Choice of clear or tinted lower dome
- 24vac input into enclosure, AC 24V feed to camera inside enclosure provided
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RX550N and SNC-RZ25N cameras

PRESSURIZED HOUSING

UNI-OPL7C2 (clear)
UNI-OPL7T2 (tinted)

- Pressurized outdoor dome, UV protected
- Eliminates condensation, bugs and other debris
- Great corrosion protection, perfect for coastlines, and other extreme environmental conditions
- 5-7 psi pressure relief valve
- IP67
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate, clear or tinted lower dome
- 24vac input via multi-pin connector
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RX550N and SNC-RZ25N cameras

VANDAL RESISTANT HOUSING

UNI-ORL7C2 (clear) • UNI-ORL7T2 (tinted)

- Outdoor dome, UV protected
- Strong cast aluminum top and trim ring
- Rugged polycarbonate lower dome
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct, clear or tinted lower dome
- 24vac input into enclosure, AC 24V feed to camera inside enclosure provided
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RX550N and SNC-RZ25N cameras



WIRELESS READY - Normal Housing

UNI-ONL7C2W (clear) • UNI-ONL7T2W (tinted)

- Outdoor dome, UV protected
- Wireless antenna cable included with housing, female N-connector on dome, cable with MMCX connector in enclosure to connect directly to optional SNCA-CFW1
- To be used with SNCA-CFW1 wireless card. (Purchased separately) - 2 foot cable with N-connectors included. SNCA-AN1 antenna or user provided antenna may be used. (Purchased separately)
- Thermostatically controlled heater
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate lower dome
- Choice of clear or tinted lower dome
- 24vac input into enclosure, AC 24V feed to camera inside enclosure provided
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RX550N and SNC-RZ25N cameras



WIRELESS READY

Vandal Resistant Housing

UNI-ORL7C2W (clear lower dome)
UNI-ORL7T2W (tinted lower dome)

- Outdoor dome, UV protected
- Wireless antenna cable included with housing, female N-connector on dome, cable with MMCX connector in enclosure to connect directly to optional SNCA-CFW1
- To be used with SNCA-CFW1 wireless card. (Purchased separately) - 2 foot cable with N-connectors included. SNCA-AN1 antenna or user provided antenna may be used.
- Strong cast aluminum top and trim ring
- Rugged polycarbonate lower dome
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct, clear or tinted lower dome
- 24vac input into enclosure, AC 24V feed to camera inside enclosure provided
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RX550N and SNC-RZ25N cameras

