



Outdoor housing for SNC-RZ50N; SNC-RZ30N



SNC-RZ30N

NORMAL HOUSING

UNI-ONS7C1 (clear lower dome)
UNI-ONS7T1 (tinted lower dome)



- Outdoor dome, UV protected
- Thermostatically controlled heater
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate lower dome
- Choice of clear or tinted lower dome
- Includes internal power supply, for 12vdc camera power
- 24vac input to enclosure
- DC 12V with pre-terminated cable/plug for camera inside enclosure
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RZ50N and SNC-RZ30N cameras

VANDAL RESISTANT HOUSING

UNI-ORS7C1 (clear)
UNI-ORS7T1 (tinted)



- Outdoor dome, UV protected
- Strong cast aluminum top and trim ring
- Rugged polycarbonate lower dome
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct, clear or tinted lower dome
- 24vac input into enclosure
- DC 12V with pre-terminated cable/plug for camera inside enclosure
- Includes internal power supply, for 12vdc camera power
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RZ50N and SNC-RZ30N cameras

PRESSURIZED HOUSING

UNI-OPS7C1 (clear) • UNI-OPS7T1 (tinted)

- Pressurized outdoor dome, UV protected
- Eliminates condensation, bugs and other debris
- Great corrosion protection, perfect for coastlines, and other extreme environmental conditions
- 5-7 psi pressure relief valve
- IP67
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate, clear or tinted lower dome
- 24vac input via multi-pin connector
- DC 12V with pre-terminated cable/plug for camera inside enclosure
- Includes internal power supply, for 12vdc camera power
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RZ50N and SNC-RZ30N cameras



WIRELESS READY - Normal Housing

UNI-ONS7C1W (clear) • UNI-ONS7T1W (tinted)

- Outdoor dome, UV protected
- Wireless antenna cable include with housing, female N-connector on dome, cable with MMCX connector in enclosure to connect directly to optional SNCA-CFW1
- To be used with SNCA-CFW1 wireless card. (Purchased separately) - 2 foot cable with N-connectors included. SNCA-AN1 antenna or user provided antenna may be used. (Purchased separately)
- Thermostatically controlled heater
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct polycarbonate lower dome
- Choice of clear or tinted lower dome
- 24vac input into enclosure
- DC 12V with pre-terminated cable/plug for camera inside enclosure
- Includes internal power supply, for 12vdc camera power
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RZ50N camera



WIRELESS READY - Vandal Resistant Housing

UNI-ORS7C1W (clear lower dome)
UNI-ORS7T1W (tinted lower dome)

- Outdoor dome, UV protected
- Wireless antenna cable include with housing, female N-connector on dome, cable with MMCX connector in enclosure to connect directly to optional SNCA-CFW1 wireless card (Purchased separately)
- To be used with SNCA-CFW1 wireless card. (Purchased separately) - 2 foot cable with N-connectors included. SNCA-AN1 antenna or user provided antenna may be used.
- Does not include antenna mount
- Strong cast aluminum top and trim ring
- Rugged polycarbonate lower dome
- Thermostatically controlled heaters
- 24 Hour fan operation for effective heating and condensation protection
- Optically correct, clear or tinted lower dome
- 24vac input into enclosure
- DC 12V with pre-terminated cable/plug for camera inside enclosure
- Includes internal power supply, for 12vdc camera power
- Pendant mount, 11/2" NPT quick connect coupling
- Accepts the SNC-RZ50N camera



Sold by:

