



Conference phones for every situation

The Konftel 200AUX – starting point for flexible phone meetings



NEW! The Konftel 200AUX is the worlds first conference phone for use with wireless headsets.



Konftel 200AUX features

- Full Duplex Crystal clear sound provided by OmniSound® technology
- A sophisticated unit, simple to connect and use
- Connects to an analog line
- Large illuminated display
- Keypad
- User-friendly menu system with phonebook for 50 numbers
- Expansion microphones and remote control options available
- Connects to an optional wireless headset
- 2 year warranty

The Konftel 200AUX is a powerful and versatile conference phone. Perfect for small and medium sized conference rooms as it can be easily upgraded with expansion microphones for greater range. A wireless headset can be directly connected to the Konftel 200AUX allowing for one participant to attend the meeting at larger distance, for example lecturing.

Now you can hold a meeting anytime – regardless of distance and pressing schedules. Konftel conference units are all equipped with the unique OmniSound® feature – optimal sound for natural, crystal clear communication. Konftel telephone conferencing brings people together and is the ideal alternative to travel.

Powerful and expandable

KONFTEL 200AUX

The Konftel 200AUX delivers perfect sound quality in conference rooms up to 300 sq ft (30 m²). For larger rooms the range can be increased by the use of optional expansion microphones and wireless headset.



User-friendly functions

The Konftel 200AUX menu system appears in the clear, illuminated graphic display. It features a keypad including mute key and a flash key for multi-party calls. The easy to use menu provides volume settings for the speakers, in addition to date, time and call time. You can even select a language!

Expandable range

Wireless headset and expansion microphones can be connected to the Konftel 200AUX providing increased range and optimal sound conditions in small and medium sized conference rooms. The remote control accessory allows for mobility during presentations and permits the user to control the Konftel 200AUX functions, such as speed dialing and volume levels.

OmniSound® – crystal clear sound

Walk and talk freely around your room with consistent high quality sound. There is no irritating sound clipping, damping or echoes. OmniSound® produces full-duplex natural sound as well as 360° sound pick-up and reproduction. An ultra-sensitive microphone provides omnidirectional transmission and three built-in surround speakers provide crystal clear reception throughout the room.



TECHNICAL DATA

Item no.: 840101060.

Power supply: Transformer 120 V AC/12 V DC.

Tele connection: Analog PBX or PSTN, RJ-11.

Power and network cable: 24.5 ft (7.5 meters), RJ-11 (tele), EIAJ class IV (electricity).

Auxiliary port: Cable RJ-45 for connection of wireless headset is included. Compatible with GN 9350 and 9120 series.

Rec. room conditions: Reverberation time: < 0.5 sec. Background noise: < 45 dBA.

Reception area: Microphone < 300 sq ft (30 m²).

Temperature: 41°–104° Fahrenheit.

Relative humidity: 20%–80% condensation free.

Approval: FCC and UL.

Size: 9.15 inches (232 mm) diameter.

Weight: 1.6 lbs.

Color: Mineral black.

OPTIONAL

900102040 Extension microphones increase the range to 750 sq ft (70 m²).

900102038 Remote control.

900103339 Extension cable, electrical, 33 ft (10 meters).

900103340 Extension cable, tele, 33 ft (10 meters).

900103341 Extension cable, electrical and tele, 24.5 ft (7.5 meters).

9146030 Wall mounting bracket.

149110 Ceiling mount suspension.

900102067 Travel case.

WARRANTY

2 year warranty.

Read more at www.konftel.com about the Konftel 200AUX and other Konftel products.



KONFTEL

North American office: Konftel, 2299 Cottonwood Dr. Elgin, IL. 60123 USA
Phone: +1 866 606-4728, Fax: +1 866 522-4278, konftel.usa@konftel.com, www.konftel.com
Head office in Sweden: Konftel AB, Box 268, SE-901 06 Umeå, Sweden
Phone +46 90 70 64 89, Fax +46 90 13 14 35, info@konftel.com, www.konftel.com

