


CASCADABLE MULTISWITCH

DMK55124F 12-Way Multiswitch

Satellite USA is now offering the new cascadable multiswitch for Dish Networks DishPro  system. The multiswitch is available in a twelve output model that can be cascaded to hundreds of connections. The multiswitch has four satellite inputs and one terrestrial input, which can be used for an off-air antenna, a cable signal/modem or a modulated signal. The DMK 55124F must be used with the System Launch Amplifier, SLA 5530NF, to guarantee that the proper dB levels are maintained throughout the system.

For system design assistance, please do not hesitate to contact us. In addition, please view the examples section on our website for system layouts.

FREQUENCY RANGE	
TERR	5 ... 862 MHz
SAT-IF	950 ... 2200 MHz
THROUGH LOSS	
TERR	3.5 ... 5 dB
SAT-IF	1.5 ... 5 dB
TAP LOSS	
TERR	20 ... 25 dB
SAT-IF	15 ... 21 dB
ISOLATION	
of taps	> 27 dB
of trunkline	> 30 dB
PRODUCT DIMENSIONS	
	5.1" (W) X 7.2" (H) X 1.3" (D)



ZSV2S - PUSH-ON F CONNECTOR

THROUGH LOSS	0.2 dB
--------------	--------

* Note: Includes 5 per pack

 **Lead Free**
Made in Germany

325 LOC CANOE CIRCLE
STEVENSVILLE, MD 21666
TEL: 410.643.6535
WEB: WWW.SATELLITEUSA-ELECTRONICS.COM

Sold by:


TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 389-0000