

# Polycom<sup>®</sup> SoundPoint IP<sup>®</sup> 450

Mid-Range SIP desktop phone with Polycom HD Voice™



# Three-line desktop phone featuring Polycom HD Voice and productivity enhancing applications through a high-resolution, graphical backlit display.

The SoundPoint IP 450 desktop phone is designed to bring advanced telephony features and applications to cubicle/office workers handling a moderate volume of calls. With its high-resolution, graphical backlit display supporting multiple languages and Asian characters, applications enabled XML Microbrowser, and Polycom HD Voice, the SoundPoint IP 450 sets new standards for the mid-range SIP desktop phone.

# **Unsurpassed Voice Quality and Clarity**

The SoundPoint IP 450 features Polycom HD Voice, bringing life-like richness and clarity to every call. Polycom HD Voice incorporates wideband audio for over twice the voice clarity, Polycom's patented Acoustic Clarity Technology for crystal-clear, noise and echo-free sound, plus best-in-class system design for high-fidelity voice reproduction.

# **Easy-to-Use Features and Applications**

An enterprise-grade phone, the SoundPoint IP 450 delivers an easy-tonavigate menu and a combination of 17 dedicated hard keys and four content sensitive soft keys on a backlit, multi-level grayscale 256 x 116 pixel LCD display. Hosting a built-in XML Microbrowser, the SoundPoint IP 450 offers an easy- to-access graphical interface to run productivity-enhancing third-party applications using Polycom's flexible and open XML API.

## Make Great Things Happen with Polycom SoundPoint IP 450

In today's Internet driven world, the ability to conduct real time communication and collaboration has become critical to an organizations survival. As the market leader in voice, video, data and Web solutions, our award-winning IP telephony and conference technology makes it easy for people to interact and maximize productivity over any network, in just about any environment, anywhere around the globe. That's why more organizations worldwide use and prefer Polycom IP telephony and application solutions. Because when people work together, great things happen. See how you, too, can achieve great things with the Polycom SoundPoint IP 450 desktop phone.

### **About Polycom**

Polycom, Inc. (Nasdaq: PLCM) is the global leader in telepresence, video, and voice solutions and a visionary in communications that empower people to connect and collaborate everywhere. Please visit www.polycom.com for more information.

#### Benefits

- ► Polycom HD Voice Unparalleled voice clarity to make your calls more efficient and productive.
- High-Quality Display High-resolution graphical 256 x 116 pixel grayscale LCD with adjustable backlighting, applications and Asian character support.
- ► Applications Enabled Built-in XML Microbrowser to run Polycom Productivity Suite and open API for productivityenhancing third-party applications.
- Broad and Robust Interoperability - Certified to interoperate with a broad array of SIP call control platforms to enable open choices and innovations while simplifying provisioning, management, and support.







# Polycom® SoundPoint IP® 450 Specifications

#### Lines (Directory Numbers)

Up to 3 lines with up to 2 concurrent calls per line

- 256 x 116-pixel backlit grayscale graphical LCD
- LED backlight with custom intensity control

#### Feature Keys

- 4 context-sensitive "soft" keys
- 17 dedicated "hard" keys
  - 3 line keys with bi-color (red/green) LED
  - 3 feature kevs
  - 5 display/menu navigation keys
  - 2 volume control keys
  - Mute, headset and hands-free speakerphone
  - Dedicated hold key

#### **Headset and Hearing Aid Compatibility**

- Dedicated RJ-9 headset port
- Amplified headsets are recommended
- Compliant with ADA Section 508 Recommendations: Subpart B 1194.23 (all)
- Hearing Aid Compatible (HAC) handset for magnetic coupling to approved HAC hearing aids
- Compatible with commercially-available TTY adapter equipment

#### **Audio Features**

- Polycom HD Voice technology delivers life-like voice quality for each audio path - the handset, the hands-free speakerphone, and the optional
- Full-duplex hands-free speakerphone
  - Type 1 compliant with IEEE 1329 full duplex
- Frequency response 150Hz 7kHz for handset, optional headset1 and hands-free speakerphone modes
- Codecs: G.722 (wideband), G.711  $\mu$ /A, and G.729A (Annex B)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation/DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Acoustic echo cancellation
- Background noise suppression

# Call Handling Features<sup>2</sup>

- Shared call/bridged line appearance
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Busy Lamp Field (BLF)
- Distinctive incoming call treatment/call waiting
- Call timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial, redial
- Call waiting
- Remote missed call notification
- Intercom
- Automatic off-hook call placement

#### Do not disturb function

#### Other Features

- Integration with Microsoft LCS 2005 for telephone and presence<sup>3</sup>
  - Compatibility with Microsoft Office Communicator and Windows® Messenger 5.1 Clients
- Enabled for Polycom Productivity Suite
- Local feature-rich GUI
- Time and date display
- User-configurable contact directory and call history (missed, placed, and received)
- Customizable call progress tones
- Wave file support for call progress tones
- Unicode UTF-8 character support. Multilingual user interface encompassing Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish,

### Protocol Support

IETF SIP (RFC 3261 and companion RFCs)

### Network and Provisioning

- Two-port Ethernet Switch
  - 10/100Base-TX across LAN and PC ports
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS4 server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported
- Web portal for individual unit configuration
- QoS Support IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DSCP
- Network Address Translation (NAT) support -
- RTCP support (RFC 1889)
- Event logging
- Local digit map
- Hardware diagnostics
- Status and statistics

### Security<sup>2</sup>

- Transport Layer Security (TLS)3
- Encrypted configuration files<sup>3</sup>
- Digest authentication
- Password login
- Support for URL syntax with password for boot server4
- HTTPS secure provisioning<sup>4</sup>
- Support for signed software executables<sup>4</sup>

- Built-in, auto-sensing IEEE 802.3af Power over Ethernet (Class 2)
- External Universal AC adapter (24VDC/12W)<sup>5</sup>

## Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- AS/NZS CISPR 22 Class B
- VCCI Class B
- FN55024
- EN61000-3-2; EN61000-3-3

#### NZ Telepermit

- ROHS compliant
- GOST-R

## Safety

- UL 60950-1
  - CE Mark
- CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1
- IFC 60950-1
- AS/NZS 60950-1

#### **Operating Conditions**

- Temperature: +10 to 40°C (+50 to 104°F)
- Relative Humidity: 20% to 85%, noncondensing

#### Storage Temperature

 $-40 \text{ to } +70^{\circ}\text{C} (-40 \text{ to } +160^{\circ}\text{F})$ 

#### SoundPoint IP 450 Comes With:

- SoundPoint IP 450 console
- Handset with handset cord
- Base stand
- Network (LAN) cable
- Universal Power Adapter (including country specific cord kit)5
- Quick Start Guide
- Product registration card

8.5 x 6 x 6.5 in x 2.5 in (21.5 x 15 x 16.5 x 6.5 cm)  $(W \times H \times D \times T)$ 

# Part Numbers/UPC Codes

- 2200-12450-001/610807687887 for NA, TWN
- 2200-12450-002/610807690214 for Japan
- 2200-12450-012/610807690221for AU, NZ
- 2200-12450-015/610807690238 for UK, HK, Singapore and Malaysia
- 2200-12450-016/610807691396 for Korea
- 2200-12450-022/610807691396 for China
- 2200-12450-122/610807690245 for ROE
- 2200-12450-025/610807687894 PoE version

# Box Dimensions/Weight

- 12.5 x 13.25 x 3.5 in (31.75 x 33.5 x 9 cm)
- $(L \times W \times H)$
- Unit weight 2.4 lbs (1.1 kg) 4.4 lbs (2.0 kg) - includes all packaging material

# Master Carton Quantity

- - Five Country of Origin
- Thailand

# Warranty

- One year
- 1. To enjoy all the benefits of Polycom HD Voice when using the phone in the headset mode, you must use a wideband
- 2. Most software-enabled features and capabilities must be supported by the server, Please contact your IP PBX/ Softswitch vendor or service provider for a list of supported features.
- 3. Requires SIP version 3.1.0 Rev C or higher.
- Requires BootROM version 4.1.2 or higher.
- Universal power adapter not included in the PoE version (P/N: 2200-12450-025)

# Find out more

Learn what Polycom VoIP Desktop Phones can do for your organization. Visit us at polycom.com or contact your Polycom representative.

Polycom and the Polycom logo design are registered trademarks of Polycom, Inc. in the U.S. and various countries.

All other trademarks are the property of their respective owners. Information in this document is subject to change without notice.

©2008 Polycom, Inc. All rights reserved.

POLYCOM<sup>®</sup> www.polycom.com

Polycom Headquarters 4750 Willow Road Pleasanton, CA 94588 1.800.POLYCOM or +1.925.924.6000

Polycom EMEA

270 Bath Road Slough Berkshire SL1 4DX +44 (0)1753 723000 Polycom Asia Pacific

8 Shenton Way #11-01 Temasek Tower Singapore 068811 +65.6389.9200

