

Recessed Ceiling Housings for Fixed Cameras SNC-CS50N, SNC-Z20N, SNC-CS11, SNC-CS10



SNC-CS50N



SNC-Z20N



SNC-CS11



SNC-CS10

UNI-IFF7C3

- 7" diameter dome indoor recessed ceiling housing
- Clear lower dome
- White trim ring
- No electronics. Interface wiring (ethernet, sensor I/O, power provided by user)
- Plenum rated metal top



UNI-IFF7T3

- 7" diameter dome indoor recessed ceiling housing
- Tinted lower dome
- White trim ring
- No electronics. Interface wiring (ethernet, sensor I/O, power provided by user)
- Plenum rated metal top
- Light loss is 1.2 F-Stop maximum

Pendant Mount Mini Dome Brackets



SNC-DF70N



SSC-CD73V



SNC-DF80N



SSC-CD75



SSC-CD77

UNI-MDB1

- Pendant mount bracket for the SNC-DF70N or the SSC-CD73V, gooseneck wall mount bracket included
- 1" NPT
- Gooseneck wall mount installs directly to wall or UNI-PMA1, UNI-CMA1, UNI-PBU1
- Die-cast aluminum construction on Mini Dome adaptor



UNI-MDB2

- Wall mount or pendant mount for the SNCDF80N, SSC-CD75 and SSC-CD77
- All aluminum construction
- 1" pipe thread for pendant mounting
- Gooseneck bracket for wall mounting
- Indoor or outdoor use



Power Block Unit

UNI-PBU1

- 220V/110Vac input, 84va capacity
- Rugged outdoor NEMA box
- 24vac output for camera, heater and blower
- Fused protected output
- Hinged door for easy access
- UNI-WMB1, UNI-MDB1 and UNI-MDB2 mounts directly to the hinged access panel.

