# Component Specifications

Part Numbers
5D460-XXX 6D460-XXX

# SlimLine Patch Cords

# **APPLICATION**

Patching and connecting cords designed for high density panels and switches. Leviton's SlimLine patch cords are bootless and feature a narrow profile to support traditional and today's high-density applications. Snagless plug design makes Leviton's SlimLine Patch Cords an excellent choice in environments where moves, adds, and changes are frequent.

# **FEATURES**

- CAT 5e or CAT 6 Component-Rated
- Snagless plug design
- · Stranded conductor for longer flex life
- · Improved strain relief
- · Improved plug access in tight spaces

#### STANDARDS COMPLIANCE

Meets all applicable standards: UL Listed, complies with all TIA/EIA-568B.2 (CAT 5e) and TIA/EIA-568B.2-1 (CAT 6) requirements, and meets FCC Part 68.

#### **PHYSICAL SPECIFICATIONS**

**Dimensions:** 3', 5', 7', 10', 15', and 20' lengths

Materials: 24 AWG, UTP stranded conductor, modular

non-keyed, 8-position, 8-conductor plug,

94V-0 rated

Colors: White, Yellow, Red, Blue, Green, Grey, Black

# **DESIGN CONSIDERATIONS**

- TIA/EIA channel performance limits total length of patching and equipment cords to 32 feet (10 meters) per TIA/EIA-568-B
- · A variety of colors for color-coding or organization
- Available in six standard lengths

#### WARRANTY INFORMATION

For a copy of Leviton product warranties, visit www.levitonvoicedata.com/warranty.

#### TYPICAL SPECIFICATION

Patch cords shall meet or exceed requirements for CAT 5e performance described in TIA/EIA-568B.2, or CAT 6 performance described in TIA/EIA-568B.2-1. Patch cords shall be stranded conductor with an 8 position modular plug on each end. The cords shall be available in 3', 5', 7', 10', 15', and 20' lengths.

# **ELECTRONIC FILES**

For CAD files, Typical Specs, or Dimensional Line Art (.DXF, .DWG, MS-DOS.eps or .TXT), visit www.levitonvoicedata.com.



# PART NUMBERS

SlimLine Patch Cords	Part No.
Cat 5e, 3-foot length	5D460-03*
Cat 5e, 5-foot length	5D460-05*
Cat 5e, 7-foot length	5D460-07*
Cat 5e, 10-foot length	5D460-10*
Cat 5e, 15-foot length	5D460-15*
Cat 5e, 20-foot length	5D460-20*
Cat 6, 3-foot length	6D460-03*
Cat 6, 5-foot length	6D460-05*
Cat 6, 7-foot length	6D460-07*
Cat 6, 10-foot length	6D460-10*
Cat 6, 15-foot length	6D460-15*
Cat 6, 20-foot length	6D460-20*

<sup>\* =</sup> Colors: White (W), Yellow (Y), Red (R), Blue (L), Green (G), Grey (S), Black(E)





For Technical Support Call 1-425-485-4288; in USA call 1-800-824-3005. Spec sheets and updates are also available at www.levitonvoicedata.com.

2222 – 222nd St. SE • Bothell, WA 98021 USA Tel: 1-800-722-2082 / 1-425-485-4288 • Fax: 1-425-483-5270 • Int'l Fax: 1-425-485-9170

