

64MB

The Messager[®] USB is a state-of-the-art digital audio playback device designed to provide a continuous-play audio source for message-on-hold, background music, or any other audio application where high-quality audio playback is required.

Messages are stored on industry standard USB flash drives from 16MB up to 4GB. The Messager USB is capable of MP3 file playback from 8Kbps all the way up to full CD-quality audio playback of 128Kbps.

Audio content is easily managed Flash Drive by plugging the USB flash drive Included! into a PC or MAC computer's USB port and "dragging and dropping" MP3 files to and from the drive. Your customers can receive new updated message-on-hold and or background music programs via e-mail or ftp and update the units themselves saving you the expense of additional USB flash drives and the related mailing and tracking costs.

The Messager USB is also available with the next generation encryption software called Sonocrypt Level 3. This version of Sonocrypt

encrypts the file itself making the MP3 file unplayable anywhere except on the Messager USB. This makes the distribution of music and messaging safe, secure, and ensures against unauthorized playback.

The Messager USB features include:

- Plays MP3 files from USB Flash Drive
- Up to 4GB Flash drives supported
- No drivers or special software needed
- Playback quality up to 128Kbps
- Store up to 1024 messages
- Continuous playback
- Built-in monitor speaker
- Sonocrypt Level 3 encryption (optional)
- LED status indicator
- Exceptional dealer support
- 5-year parts and labor warranty

Each Messager USB is built to exacting quality standards using state-of-the-art assembly equipment for outstanding reliability and years of dependable service.



Specifications



Technical

Decoding MPEG (.mp3)
Frequency Response 20Hz to 20KHz
Bit Rate 8Kbps to 128Kbps
Sample Rate 16KHz to 48KHz
Memory Type USB Flash Drive
Memory Capacity 16MB to 4GB
Message Capacity Up to 1024 messages
Message Loading Computer via USB Flash Drive


Message Playback Power Supply Audio Output	. 110VAC 60Hz to 12VDC @ 500mA
	Adjustable volume control
Impedance	. 6V p-p @ 8Ω or 3V p-p @ 600Ω
Size	. 6.00" x 6.00" x 1.50" (H x W x D)
Color	. Black
Shipping Weight	. 3 pounds

Memory Tables

The <u>bit-rate</u> of your MP3 file will determine memory capacity.

64MB Flash Drive Capacity Table			
Bit-rate	Quality	Message Time (64MB)	
32Kbps	Analog Telephone	4.25 Hours	
48Kbps		2.66 Hours	
64Kbps		2.13 Hours	
96Kbps	↓	1.33 Hours	
128Kbps	CD	64 Minutes	

Back View



Copyright © 2006 by Nel-Tech Labs, Inc. • All specifications subject to change without notice. • Printed in the USA • Rev 07/06