Rectangular Stamped Steel Floor Box

HUBBELL



Hubbell introduces a new series of rectangular stamped steel floor boxes in one, two and three gang for flush connections in tile, carpet or wood floor installations. Removable barriers allow for flexible separation of power and low voltage between gangs. Larger concentric knockouts and adjustability features combine with a complete offering of the highest quality wiring devices to provide a total solution in single or multi-service applications. A variety of covers and flanges are available in brushed brass or aluminum to meet several aesthetic requirements. Rectangular stamped steel floor boxes are UL listed and CSA certified. All Hubbell floor box assemblies with flush connections comply with UL 514A scrub water specifications. Hubbell also offers a complete line of cast iron and PVC floor boxes for single and multi-service applications. For more details on these products, visit www.hubbell-wiring.com.

Features

- One, two and three gang options.
- 16 gauge stamped steel construction.
- Fully adjustable leveling option.
- Adjustable mounting brackets.
- Concentric knockouts

Benefits

- Removable barriers provide optimal capacity while maintaining separation of power/low voltage cables.
- Structural durability for both slab and above grade applications.
- · Adjustable before and after the concrete pour.
- Secures floor box in new or existing wood floor installations.
- Various knockouts ranging from ½" 1¼" N.P.T. are located on ends, sides and bottom of boxes.





) pre-garvanized sheet metal.	Corcrete and wood boxes: 16 gauge (Jb25" + U12/4) pre-galvanized sheet metal Corers: brass, aluminum, Flanges: brass, aluminum, clear polycarbonate.	SPECIFICATIONS: Concrete and wood boxes: 16 gauge (.18/25 * + Covers: brass, aluminum, Flarges: brass, aluminum, clear polycarbonate UL FILE # E31999 CSA File # LR18416		Hubbell de Mexico, S.A. de C.V. (52) 5 575-2022, Fax (52) 5 559-8626 Caribe Sales Agencies, Puerto Rico (809) 720-7185, Fax (809) 789-2796 mark of Hubbell Incorporated H5037	9) 720-7185, F	de C.V. (52) 5 5 ^o uerto Rico (809 ed	/lexico, S.A. s Agencies, F ell Incorporate	Worldwide Locations Hubbell Canada (905) 839-1138, Fax (905) 839-9108 Hubbell Canada (905) 839-1138, Fax (905) 839-9108 Hubbell Ltd. England (441) 234-854044, Fax (441) 234-854008 Hubbell Caribe Sales Agencies, Pu Hubbell-Talian Co., Ltd., (886) 2 567-5995, Fax (886) 2 567-4863 Caribe Sales Agencies, Pu Printed In U.S.A. Specifications subject to change without notice.	:54008 67-4853 ttice. ® Registerec) 839-9108 ax (441) 234-8 Fax (886) 2 50 ange without nc	38, Fax (905) 14-855444, Fa 2 567-5995, subject to cha	.ocations 1 (905) 839-11 gland (441) 23 50., Ltd., (886) Specifications	Worldwide Locations Hubbell Canada (905) 839-1138, Fax (905) 839-9108 Hubbell Ltd. England (441) 234-855444, Fax (441) 234-854008 Hubbell-Taian Co., Ltd., (886) 2 567-5995, Fax (886) 2 567-4853 Printed In U.S.A. Specifications subject to change without notice. ® F
e barriers. rub Water Tightness Tests).	floor boxes include removable removable barriers. with UL514A Section 32A (Sci	/fil:	NOTES:	51	(800) 255-103	882-4800 • FAX	-2420 • (203)	Hubbell Incorporated (Delaware) • 185 Plains Road • Milford, CT 06460-2420 • (203) 882-4800 • FAX (800) 255-1031 World Wide Web URL: http://www.hubbell-wiring.com	Hubbell Incorporated (Delaware) • 185 Plains Road • N World Wide Web URL: http://www.hubbell-wiring.com	World Wide Web URL: http://www.hut	Incorporat Id Wide Web I	Wor	HUBBELL
" prefix for covers. screws.	VA" prefix for floor boxes, "SA" rum dimension without base s	*Also available in aluminum. Use "BA" prefix for floor boxes, "SA" prefix for covers Δ Dimension B represents the minimum dimension without base screws.	KEY						me	ine-Kelle	ring Dev	e Wi	
Dimensions Inches (mm) 11.31" x 6.00" (287.3 x 152.4) 11.31" x 6.00" (287.3 x 152.4) 10.81" x 5.56" (274.6 x 141.2) 11.34" x 6.00" (288.4 x 152.4) 11.34" x 6.00" (288.4 x 152.4)	Catalog # Dimension SB3085 11.31" SA3085 11.31" S3085 10.81" SB3085W 11.34" SA3085W 11.34"	Flanges (if required) () Brass (carpet floors) () Aluminum (carpet floors) () Clear polycarbonate (carpet floors) () Brass (wood floors) () Aluminum (wood floors) ()	Flanges Brass (ca Aluminun Clear pol Brass (w Aluminun	ns Inches (mm) 10" (204.7 × 152.4) 10" (204.7 × 152.4) 10" (206.7 × 152.4) 10" (206.5 × 152.4) 10" (206.5 × 152.4)	Dimensions 8.06" x 6.00" 8.06" x 6.00" 7.56" x 5.56" 8.13" x 6.00" 8.13" x 6.00"	Catalog # SB3084 SA3084 S3084 SB3084W SB3084W	Jired) ors) et floors) nate (carpet flc ors) 1 floors)	Flanges (if required) Brass (carpet floors) Aluminum (carpet floors) Clear polycarbonate (carpet floors) Brass (wood floors) Aluminum (wood floors)	Dimensions Inches (mm) 4.84" x 6.00" (123.0 x 152.4) 4.84" x 6.00" (123.0 x 152.4) 4.84" x 5.56" (111.3 x 141.2) 4.85" x 6.00" (123.2 x 152.4) 4.85" x 6.00" (123.2 x 152.4)		Catalog # SB3083 SA3083 S3083 S3083 SB3083W SA3083W	Brass (carpet floors) Aluminum (carpet floors) Clear polycarbonate (carpet floors) Brass (wood floors) Aluminum (wood floors)	Brass (carpet floors) Aluminum (carpet floors) Clear polycarbonate (car Brass (wood floors) Aluminum (wood floors)
		(if required)	Three Gang (if required)				iges	Two Gang Flanges (if required)				anges	Single Gang Flanges (if required)
S3813* Blank	Style Line® opening	S3425 2 ³ / ₈ " for single		 S2825 21/8" for single receptacle 	I o o	© © S2625* Combination 2 ¹ / ₈ " x 1"	S2425* Combination 2 ¹ /8" x ³ /4"	$^{\circ}_{\circ}$	S3825* Duplex flap	S3625* Duplex screw 11⁄2" x 11⁄2"	$\mathbb{O} \mathbb{O} \mathbb{O}$	Covers (Suitable for use on tile or carpeted floors) All rectangular covers fit all rectangular boxes Dimension 2.99" x 4.16"	Covers (Suitable for use on tile or All rectangular covers fit rectangular boxes Dimension 2.99" x 4.16"
(6) Concentric 1⁄2",3⁄4",1",11⁄4"	(4) Concentric ½",¾",1",1¼"	(2) Concentric ½",¾",1",1¼"	icentric	c (6) Concentric 3⁄4",1",11⁄4"	(4) Concentric 3⁄4",1",11⁄4"	1/4"	(2) Concentric ¾",1",1¼"	(6) Concentric ¾",1",1¼"	(4) Concentric ¾",1",1¼"		(2) Concentric ¾",1",1¼"		Knockouts Bottom
			(2) Concentric 1/2", 3/4"		(2) Concentric 1/2", 3/4"	(1) 3⁄4"	(1) 1/2", (1) 3/4"	(1) Concentric 3/4",1",11/4"	(1) Concentric 3⁄4", 1",11⁄4"		(1) Concentric 3⁄4",1",11⁄4"		Copposite Ends
1/2",3/4",1"	1/2", 3/4", 1"	1/2",3/4",1"			1/2", 3/4"	(1) 3⁄4"	(2) 1/2", (1) 3/4"	3/4", 1", 11/4"	3/4", 1", 11/4"		3/4", 1", 11/4"		Opposite Sides
9.64" (244.9)	6.42" (163.1)		245.6)	9.67" (245.6)	6.44" (163.6)	(81.0)	3.19" (8	9.67" (245.6)	6.44" (163.6)	5	3.19" (81.0)	Inches (mm)	DimensionsC Inches (mm)
4.50 (114. 3.13" (79.5)	4.50 (114.3) 3.13" (79.5)	5)	(69.6)	4.30 2.74"	4.30 (111.2) 2.74" (69.6)	(69.6)	4.30 (1 2.74" (6	4.30 (111.2) 3.72" (94.5)	4.30 (111.2) 3.72" (94.5))	4.30 (111. <i>2</i>) 3.72" (94.5)	Inches (mm)	DimensionsA incries (mm)
42.50 (696.4) each gang	42.50 (696.4) each gang		557.2) ang	34.00 each	35.00 (573.5) each gang	647.3)	39.50 (647.3)	50.80 (832.5) each gang	52.80 (865.2) each gang			ity-(cm [°])	Cubic In. Capacity-(cm [°])
			2.7)	.50" (12.7)	.50" (12.7)	.7)	.50" (12.7)	.50" (12.7)	50" (12.7)		.50" (12.7)	ant	After Pour Internal Height Adjustment
1.00 (E0.T)	1.00 (LO.T)	1.00 (20.7)	31.8)	1.25" (31.8)	1.25" (31.8)	1.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)		1.25" (31.8)	ernal ent	Before Pour External Height Adjustment
	1 00" (OF A)		69.9)	2.75" (69.9)	2.75" (69.9)	9.9)	2.75" (69.9)	3.75" (95.3)	3.75" (95.3)		3.75" (95.3)	Min. Depth of Pour- Inches (mm)	Min. Depth of P
B2483	B2482		3	B2423*	B2422*	*	B2421*	B2433*	B2432*		B2431*		Catalog #
	Wood Floor Applications	Wood Flo			Shallow		plications	Concrete Applications	Deen				
	B2482 B2483	B2481	3	B2422 B2423	ÉÉ	B2421		32 B2433	B2432	B2431			
							options)	Rectangular Selection Options (single or multiple service options)	single or mu) ptions	ection C	<u>ular Sel</u>	Rectanç