

Sold by:



TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 389-0000

Panasonic
ideas for life



KX-NT700 IP Conference Phone

- High Definition Voice Quality with Noise Reduction Technology
- Real-Time Slow-Talk Feature for Enhanced Comprehension
- SD Card Recording for Convenient Play Back on a PC



Panasonic System Networks Company of America

Home and Business Communications

Enhanced Communications Solutions

The clear choice for more productive conference calls.

In a perfect world, all business meetings would be face-to-face.

However, in this imperfect world of tightened travel budgets, busy schedules, deadlines, traffic jams and geographically dispersed offices, telephone conferences are proven time and money savers. Now you can be sure you'll get the most out of your conferences with the Panasonic KX-NT700 IP Conference Phone. It's the next best thing to meeting in person.

High definition voice quality

The KX-NT700 uses a wideband speech codec to deliver high definition sound quality. This ensures that multiple users can engage in a conversation without compromising voice quality and delivers crystal clear sound giving your conferences an intimate, face-to-face feeling.

Real-time slow-talk

A Panasonic exclusive! This ingenious feature allows you to easily understand a fast talker by slowing down spoken words while shortening the silent intervals between them. Avoids wasted time caused by asking conference participants to repeat themselves.

SD card recording

Here's an easy way to record and review completed meetings. The KX-NT700 features an SD card slot so you can easily record your conferences to an SD card and play them back on a PC at your convenience. A 2GB SD card will record up to 67 hours of conference time!

Noise reduction

The KX-NT700 employs noise reduction technology which helps reduce ambient noise such as projector fans, ceiling music or nearby traffic so you hear the conversation, not the noise.



A co-worker that fits right in

The KX-NT700 works with your existing telephone system, or operates natively on your business or broadband data network. The system includes a Three-Party Conference feature that lets you conference up to three units together, or conference one analog call into a two-party IP conference meeting.


Need to further expand your meeting to include other remote parties? The KX-NT700 is designed to work with a variety of existing equipment for maximum flexibility including:

- TCP/IP (peer to peer)
- SIP Extension (with TDE or NCP systems only)
- Analog Telephone Line (PSTN)
- Netcam Integration (v2)*

Since the KX-NT700 supports connection to Standard (PSTN) telephone networks, it's no problem adding a remote mobile phone to the conference if someone's running late and you want to conference them in.

* PC Conference Manager Software required for Netcam support

KX-NT700 CONTROL PANEL



USB PORT


Connect to PC for Conference Manager Application.

REAL-TIME SLOW-TALK

Slow down rapid speech with the press of a button.

SD CARD SUPPORT

Record your conferences for simple playback on a PC.



AUDIO IN/OUT

3.5mm Audio Input/Output Jack for connection to:

- External audio recording devices
- Personal computers
- Wireless handsets

HIGH DEFINITION VOICE QUALITY

Full Duplex 7kHz Audio.

Get connected with video conferencing

Combine the KX-NT700 with a Panasonic IP Network Camera* and give your clients the face time they deserve without the high operating costs of business trips. Less travel also means higher productivity and reduced environmental impact.

* PC Conference Manager Software required for Netcam support



KX-NT700 Accessory:

Optional External Microphone

The KX-NT700 supports up to 2 external mics (KX-NT701)



KX-NT700 Specifications

Technical Specifications		
Analog Line Interface	I/F Connector	RJ11 x 1
	Dialing	Dial Pulse (DP) 10pps, 20pps Tone (DTMF) Dialing
Ethernet Interface	I/F Connector	RJ45 x 1
	Transceiver Type	10/100Base-T, Auto MDI/MDX
General Purpose Interface	USB Interface	USB 2.0 (Low/Full Speed) Device Function x1
	SD Slot	1
	Audio Line In/Out	ø3.5mm mini0jack x1
	I/F Connector	RJ9 x 2
Microphone Interface	External	4 Wire (Power, GND, MIC-Mute, MIC-Signal-Input)
Audio Interface	Loudspeaker	1
	Speaker Volume	Adjustable to 85dB at 0.5m
	Range of Frequency	300Hz – 7000Hz
	Stereo/Mono	Mono
	Internal Microphone	Microphone x 4 corners
	Microphone Coverage	3m Radius
	Range of Frequency	300Hz – 7000Hz
	S/N Ratio	Above 58dB at 1kHz
Display	LCD Resolution	103 x 48 Full Dot
	LCD Back Light	Yes (white)
	LCD Contrast	Yes (6-level)
Status Indicator	LED	4 (dual-colored LED red & blue)
Keypad	Function Key	F1, F2, F3
	Volume (scroll) key	UP, DOWN
	Dial Key	0-9, *, #
	Other Key	SP-Phone, Flash, Redial/Pause, Mic Noise Cut, Clear, Back, Menu, Enter
Chassis	Size	2 3/16"H x 10 1/16" W x 10 1/16" D
	Weight	2.87 lbs
Power Supply	AC Adaptor (PQLV206)	Input 85-276 / Max 0.3A Output DC9V 750mA
PoE		IEEE802.3af compliant
Power Consumption		Max 6.5W
Environment Conditions	Operating Temperature	0° C - 40°C
	Storage Temperature	-10°C - 50°C
	Relative Humidity	Less than 90% (non-condensing)

Features			
Signalling Protocol	SIP	RFC3261 and companion RFCs	
VoIP	CODEC	G.711 (A/u), G.729a, G.722 (64kbps)	
	PLC	Yes (G.711 only)	
	Silence Suppression	No	
	CNG	No	
	Jitter Buffer	Max 500ms (G.729a)	
	Packet Header Compression	No	
	QoS	IEEE 802.1 P/Q, Layer 3 TOS, Diffserv	
Network	TCP/IP, UDP, RTP	Yes	
	RTCP	Future Support	
	FTP Client	Yes	
	DHCP Client	Yes	
Telephone	Caller ID	No	
	Phonebook	100	
	Stored Dial Max. Digits	32	
	Mute	Yes	
	Flash	Yes	
	Pause	Yes	
	Redial	Yes	
	History Redial	10	
	Ringer Patterns	3	
	Ringer Volume	Off, Low, Middle, High	
	SP-Phone Volume	8 Steps	
	Programmable Tone/ Pulse	Yes	
	Multi Point Conferencing	3 points	
	All Individual Disconnect	Yes	
	Conference Recording	Recording Time Period	67 Hours (2GB SD Card)
		Number of Recordings	Maximum 100
New Message Playback		Yes	
FF/REV/STOP		Yes	
Skip/Repeat		Yes	
All Individual Erase		Yes	
	Time Stamp	Yes	

System Compatibility

Single line telephone (SLT) compatible*: KX-TDA50/100/200/600, KX-TDE100/200/600, KX-NCP500/1000

SIP extension compatible: KX-TDE100/200/600, KX-NCP500/1000

* Caller ID board recommended



Panasonic System Networks Company of America

Home and Business Communications

Three Panasonic Way,
Secaucus, NJ 07094
(201) 348 - 7000
www.panasonic.com/bts

Design and specifications subject
to change without notice.

BTS080685BR0r1