



Passport DC (Direct Connect) Headsets



- High transmit microphone for direct connect into phone systems that do not require the use of an amplifier
- Noise-canceling microphone greatly reduces background noise for a professional sounding call
- Durable construction to endure the stress of the 24/7 call center
- Virtually indestructible, highly flexible gooseneck boom. Rotates for left or right ear placement. Maintains position for consistent voice quality
- Sturdy quick disconnect allows fast and easy detachment from lower cord for greater mobility
- Adjustable headband secures positional adjustment, won't slide out of position
- Concave ear cushion for improved comfort and sound

Compatibility:

- Passport 10V-DC, 20V-DC, 37V-DC compatible with Passport V-series amplifiers and direct connect cords
- Passport 10P-DC, 20P-DC, 37P-DC compatible with VXI Passport P-series and Plantronics amplifiers and direct connect cords
- Passport 10G-DC, 20G-DC, 37G-DC compatible with VXI Passport G-series and GN Netcom amplifiers and direct connect cords



Passport 20-DC



Passport 10-DC



Passport 37-DC

2 YEAR *Unconditional* WARRANTY

TRANSMIT SPECIFICATIONS

Microphone: Noise canceling electret
 Sensitivity: -31dB @ 1kHz (defined 1" from talk-side, 82dB SPL)
 Current consumption: 200uA max
 Operating Voltage: DC 1.0V min. to 20V max.

RECEIVE SPECIFICATIONS

Speaker: Dynamic; 36mm diameter
 SPL: 90dB @ 1kHz, 0.55V input
 Impedance: 300 Ohms
 Frequency response: 200Hz to 5 kHz
 Rated input: 10mW continuous, 100mW peak

MECHANICAL SPECIFICATIONS

Cables: Standard wire, PVC insulation, polyurethane jacket
 Mic boom: Flexible, with positioning memory; swivels 270°
 Mounting: Left or right ear placement
 Headband: Stainless steel, adjustable; ratchet positioning