

Exceptional Features and Performance in a Featured, Expandable Response Point Phone

The Aastra 6753i RP offers enterprise-grade performance, flexibility, expandability and value in a robust telephone for the AastraLink RP™, a Microsoft® Response Point™ phone system designed especially for small businesses that have 1 to 50 employees. Sporting the unique Response Point blue button and equipped with a 3 line backlit LCD display, the sleek and stylish 6753i RP supports up to 6 lines/users, offers headset support, provides full integration with the Response Point software and delivers carrier grade performance to small business.

Part of the 675xi RP series of telephones, the 6753i RP is ideally suited for frequent use small business applications where multi-line, high-quality communication is required.



Key Features and Benefits:

» Response Point Support

The Aastra 6753i RP has been designed to tightly integrate with the AastraLink RP™ phone system and fully supports SP1 enhancements. The phone seamlessly responds to system features such as auto-discovery and auto-configuration at start up to easily allow additional phones to be added to the system. The Response Point blue button initiates a host of advanced voice activated features such as call dialing, forwarding, transferring, parking and directory access.

» Enhanced Call Management

With extensive storage capacity for caller logs and redial lists, the Aastra 6753i RP can improve efficiency by providing more call information with the push of a button. Six programmable buttons with LED's, two line/call appearance buttons with LED's, eight dedicated hard keys and four navigational keys provide more flexibility in making and receiving calls and accessing information. Headset support with built-in amplifier provides additional flexibility for small business users.

» Expandability

The Aastra 6753i RP supports up to three Aastra M670i (536M) expansion modules, each offering 36 keys with LED indicators to create a feature rich attendant console.

» Remarkable Audio

All Aastra RP telephones offer a full-duplex speakerphone with excellent voice clarity and delivery. Incorporating the industrial design of Aastra's proven enterprise grade 5i Series of IP telephones; it's no surprise that superior voice quality is a hallmark of the Aastra 675xi RP family.

» XML Browser and More

The Aastra RP telephones are equipped with a variety of additional features that can improve business efficiency, provide flexibility and enhance Small Business telephony. All RP telephones are equipped with XML browser capabilities allowing access to customized services and applications. Create internal service applications to customize the phone to meet your specific needs or to develop vertical applications using the display and keypad. Other highlights for the Aastra 6753i RP include POE support, larger backlit LCD displays and LED indicators, and four position foot stands.

Feature Highlights

- » Up to 6 lines/users phone
- » Full-duplex quality speakerphone
- » Call Hold
- » Call forward
- » Call transfer
- » Call waiting
- » Call timer
- » Caller and calling line information
- » Callers log
- » 3-way Conference
- » Redial list
- » Do Not Disturb
- » Live dial pad support
- » Missed Call Notification
- » XML browser*

* Feature availability is independent of Microsoft Response Point platform

Feature Keys

- » 2 line/call appearance buttons with LEDs, programmable up to 6 lines
- » Response Point button for voice activated commands/dialing
- » 4 navigational keys
- » Up to 6 programmable buttons with LEDs
- » 8 dedicated hard keys including Hold, Redial, Speakerphone/Headset toggle, Mute, Options, Goodbye, 2 volume keys

Audio and Codecs

- » Hearing aid compatible (HAC) handset
- » Full-duplex quality speakerphone
- » G.711 μ -law / A-law
- » G.729
- » Independent volume setting for handset/speaker/headset
- » Echo cancellation
- » Comfort noise generation
- » Codec packet loss concealment
- » Modular (RJ22) Headset Connector with built-in amplifier
 - Non-amplified business headsets are recommended

Display and Indicator

- » 3 line adjustable backlit LCD display LED for call and message waiting indication

Management and Security

- » Embedded Web interface available for additional phone customization
- » User and administrator level passwords for login
- » HTTP/HTTPS web management
- » Phone lock with PIN
- » Response Point administrator

XML API Capabilities*

- » Display control based on user actions or on events
- » Dynamic Phone Configuration
- » RTP Streaming control

- » CTI applications
 - See XML API Documentation for more details

Expansion Modules

- » Supports up to 3 M670i (536M)² modules

Localization

- » Multi-lingual support capable

Protocols

- » IETF SIP (RFC3261) and associated RFCs

Networking

- » Dual 10/100 Mbps switched Ethernet ports
- » Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
- » Quality of Service (QOS) support – IEEE 802.1 p/Q VLAN and priority tagging, Type of Services (TOS), and Differentiated Services Code Point
- » Integrated HTTP/HTTPS server for web administration and maintenance including a built-in troubleshooting section

Power

- » AC adapter (48V DC) included
- » Integrated IEEE 802.3af Power Over Ethernet (PoE) support

Package Contents

- » Aastra 6753i RP phone
- » Handset and coil cord
- » 2 x Foot stand
- » AC adapter
- » Ethernet cable
- » Programmable keys label
- » Wall mounting kit
- » Installation Guide

Physical

- » 23.5 cm W x 20.8 cm D x 8.0 cm H (9.3"W x 8.2"D x 3.2"H)
- » 895 g (31.3 oz)

- » 4 positions footstand
- » Wall mountable

Operating Conditions

- » Operating Conditions:
 - Temperature: 0°C to 50°C (32°F to 122°F)
 - Relative Humidity: 20% to 90%, non-condensing
- » Storage Temperature: -50°C to 70°C (-58°F to 158°F)

Regulatory

CE /Europe

- » ROHS compliant
- » WEEE (2002/96/EC)
- » CE Mark (89/336/EEC EMC Directive and 73/23/EEC Low Voltage Directive)

EMC

- » FCC Part 15 Class B
- » ICES-003 Class B
- » VCCI Class B
- » AS/NZS 3548 Class B
- » EN55022 Class B
- » CISPR22 Class B
- » EN55024
- » EN61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11

Safety

- » CAN/CSA C22.2 No. 60950
- » EN 60950
- » UL 60950-1

Telecom

- » FCC Part 68 (Hearing Aid Compatibility)
- » AS/ACIF 5004

Part Numbers

- » A1753-0135-10-01 – 6753i RP Phone, English Text Keypad, North America (120V) power adapter

* Feature availability is independent of Microsoft Response Point platform

² Some products may reflect former name

Rev 07/08

COPYRIGHT (C) 2008 AAastra TECHNOLOGIES LTD. ALL RIGHTS RESERVED. INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. AAastra TELECOM ASSUMES NO RESPONSIBILITY FOR ANY ERRORS THAT MAY APPEAR IN THIS DOCUMENT. PRODUCT CAPABILITIES DESCRIBED IN THIS DOCUMENT PERTAIN SOLELY TO AAastra TELECOM'S MARKETING ACTIVITIES IN THE U.S AND CANADA. AVAILABILITY IN OTHER MARKETS MAY VARY.

AAastra IS A REGISTERED TRADEMARK OF AAastra TECHNOLOGIES LTD. MICROSOFT, MICROSOFT OFFICE OUTLOOK AND RESPONSE POINT ARE TRADEMARKS OF THE MICROSOFT GROUP OF COMPANIES IN THE UNITED STATES AND/OR OTHER COUNTRIES.

AAastra TELECOM

155 SNOW BLVD.,

CONCORD, ONTARIO, CANADA, L4K 4N9

SALES@AAastra.COM • WWW.AAastrATELECOM.COM