

Product Specifications



2512CAT5PS2-48

Material ID: 108236167

PowerSUM 2512 Category 5 U/UTP Modular Patch Panel, 48 port 100BASE-TX, 100BASE-T



CHARACTERISTICS

Dimensions

Depth	40.64 mm		1.60 in
Height	88.90 mm		3.50 in
Width	482.60 mm		19.00 in

Electrical Specifications

ANSI/TIA Category	5
-------------------	---

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	UL/cUL listed
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Cable Type	U/UTP (unshielded)
Product Type	Panel
Total Ports, quantity	48
Color	Black
Package, quantity	1
Rack Type	EIA 19 in
Rack Units	2

Mechanical Specifications

Material Type	High-impact, flame retardant, thermoplastic Powder-coated steel
---------------	---

Product Specifications

2512CAT5PS2-48



Regulatory Compliance/Certifications

Agency

RoHS 2002/95/EC
ISO 9001:2000

Classification

Compliant
Compliant



SYSTIMAX®
SOLUTIONS
www.commscope.com

©2009 CommScope, Inc. All rights reserved.
All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope.
All specifications are subject to change. See www.commscope.com for the most current information.

page 2 of 2
6/8/2009