Product Specifications



760007047

Pre-Radiused SC Connector for 3.0 mm Fiber Cordage, multimode



CHARACTERISTICS

Construction Materials

Fiber Type LazrSPEED \$ 150, 50 μ m multimode fiber | LazrSPEED \$ 300, 50 μ m multimode

fiber | LazrSPEED® 550, 50 μm multimode fiber | OptiSPEED®, 62.5 μm

multimode fiber

Ferrule Geometry Pre-radiused Ferrule Material Zirconia

Dimensions

Compatible Cable Diameter 3.0 mm | 0.1 in Length 56.0 mm | 2.2 in

General Specifications

Interface SC
Body Style Simplex
Interface Feature Standard
Color Beige
Package, quantity 1

Mechanical Specifications

Cable Retention Strength, maximum 5.10 kg @ 0 $^{\circ}$ 11.24 lb @ 0 $^{\circ}$

Optical Performance

Insertion Loss Change, mating 0.30 dB
Insertion Loss Change, temperature 0.30 dB
Insertion Loss, typical 0.30 dB
Return Loss, maximum 20.0 dB

Optical Specifications

Optical Components Standard ANSI/TIA/EIA-568-B.3

Regulatory Compliance/Certifications

AgencyClassificationRoHS 2002/95/ECCompliantISO 9001:2000Compliant



Product Specifications





* Footnotes

Insertion Loss Change, mating Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from 0 °C to +60 °C (+32 °F to +140 °F)



