

Floor and Wall Boxes Accessories

Protective Ring for 2¹/₈"
Threaded Cover



S3061

Theater Seating Floor Box



F3185


Adjustable Tops (Brass)



F1339



F1539



Adjustable Tops

Coupling (Brass)



F1340

Problem Solvers & Replacement Components Protective Ring for 2¹/₈" Threaded Covers

Description	Catalog Number
Provides mechanical and wet mop protection for plugs and receptacles (brass).	S3061

Theater Seating Floor Box

Description	Catalog Number
The theater seating floor box is nonadjustable and provides a 3/4" threaded hub for conduit connection to theater aisle lights. It permits opening of the enclosure for wiring without disturbing above floor connections. Other features include a cast iron box with a corrosion-resistant finish and a blank steel cover. Knockouts: (3/4" surface, 3/4" sides, 3/4" bottom) 18.80 cu. in. (380 cubic cm.).	F3185

Adjustable Tops (Brass)

Brass Outlet Fittings for Conduit Systems.

Future requirements for floor outlets may be accommodated by systematically studding the floor with these fittings, all radiating from one or more floor boxes, from which any changes or additions may be subsequently made by the pulling of wires from box to the outlet. Adjustment tops are male connections to be mounted on elbow or tee fittings. They provide a pre-pour adjustment and an available connection for above-floor service heads.

Description	A	B	Catalog Numbers
3/4" threaded conduit size (male).	1.25" (31.8)	1.44" (36.6)	F1339
1" threaded conduit size (male).	1.31" (33.3)	1.75" (44.5)	F1539

Note: Adjustment: 3/4" and 1" fittings permit 1/2" vertical adjustment.

Coupling (Brass)

Couplings are utilized for straight conduit connections when a floor box is not required. The conduit stub is brought to within approximately 1 1/4" of the planned surface, and the coupling is mounted and adjusted prior to the concrete pour. Standard service heads may be mounted to the couplings as required.

Description	A	B	Catalog Number
3/4" threaded conduit size (female).	1.44" (36.6)	1.25" (31.8)	F1340