

### SurgeGate Series Modular Protection



#### CAT6-75—CATEGORY 6 SOLID-STATE BUILDING ENTRANCE PROTECTOR



#### Features

- UL Listed for Primary (497) and Isolated Loop (497B) applications.
- Exceeds TIA/EIA Standards 568B.2-1 and 758 for category 6 performance.
- Solid-state protection provides the fastest response to transient voltages (1–5 nanoseconds) by quickly diverting damaging surges to ground.
- Use between buildings in a campus environment as a building entrance protector or in hostile industrial applications as an isolated loop protector.
- **Expandable System Protection**—SurgeGate Series Base Units and Modules can be attached to expand system protection as your system grows.
- **Lifetime Product Warranty**—This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.
- **\$50,000 Connected Equipment Warranty**—This ITW Linx product will protect your equipment or we will repair or replace it up to \$50,000!

#### Technical Specifications

*Designs and specifications are subject to change without notice due to product improvement.*

#### PRODUCT SPECIFICATIONS:

Agency Approval . . . . .	UL Primary (497) and Isolated Loop (497B)
LED Indicators . . . . .	N/A
Grounding Requirements . . . . .	Uses Electrical AC ground, for use with SurgeGate Series AC Base Units. See Technical Reference page 106–107 for additional grounding tips
Recommended Ground Impedance . . . . .	< 0.5 Ohm
Width . . . . .	4.25"
Height . . . . .	4.25"
Depth . . . . .	1.5"
Weight . . . . .	0.42 lbs
Product Warranty . . . . .	Lifetime
Connected Equipment Warranty . . . . .	Up to \$50,000



For up-to-date warranty information see our web site: [www.itwlinx.com](http://www.itwlinx.com)



#### AC SURGE PROTECTION:

SurgeGate Plus Circuitry . . . . .	N/A
Protect or Disconnect Circuitry . . . . .	N/A
Thermal Fusing . . . . .	N/A
Catastrophic Surge Circuit . . . . .	N/A
Over/Undervoltage Voltage Protection . . . . .	N/A
Overvoltage Voltage Shutoff . . . . .	N/A
Undervoltage Voltage Shutoff . . . . .	N/A
Single Pulse Energy Dissipation . . . . .	N/A
Peak Impulse Current . . . . .	N/A
EMI/RFI Noise Filtration . . . . .	N/A
Line Voltage . . . . .	N/A
Initial Clamping Level . . . . .	N/A
Clamping Level . . . . .	N/A
Protection Modes . . . . .	N/A
Maximum Current Rating . . . . .	N/A
Response Time . . . . .	N/A
Plug Configuration . . . . .	N/A
Number of Outlets . . . . .	N/A
Switched Outlets . . . . .	N/A
Cord Length . . . . .	N/A

#### SIGNAL LINE SURGE PROTECTION:

##### TELCO CIRCUIT PROTECTION

Signal Perfect Circuitry . . . . .	Yes
Fuseless/Auto-Resettable . . . . .	Yes
Clamping Level . . . . .	75V
Response Time . . . . .	1–5 Nanoseconds
Capacitance . . . . .	N/A
Suppression Modes . . . . .	N/A
Wires Protected . . . . .	4-pairs
Termination Type . . . . .	110 Punchdown

##### COAX CIRCUIT PROTECTION

Signal Perfect Circuitry . . . . .	N/A
Fuseless/Auto-Resettable . . . . .	N/A
Response Time . . . . .	N/A
Termination . . . . .	N/A
Antenna/Cable Lines Protected . . . . .	N/A
Antenna/Cable Clamping Level . . . . .	N/A
Antenna/Cable Attenuation . . . . .	N/A
Satellite Lines Protected . . . . .	N/A
Satellite Clamping Level . . . . .	N/A
Satellite Attenuation . . . . .	N/A

##### LAN CIRCUIT PROTECTION

Signal Perfect Circuitry . . . . .	Yes
Fuseless/Auto-Resettable . . . . .	Yes
Performance Rating . . . . .	Cat 6
Clamping Level . . . . .	75V
Response Time . . . . .	1–5 Nanoseconds
Capacitance . . . . .	< 20pF
Wires Protected . . . . .	4-pairs
Termination Type . . . . .	110 Punchdown



**More information is available in the Technical Reference section of this catalog, turn to page 86.**

#### Applications:

- Telephone Systems
- Cameras
- Access Controls
- Alarms
- Networks

#### Ordering Information

ITW Linx Part Number	Description	Termination Type
CAT6-75	Protects high-performance 4-pair Category 6 Outside Plant Cables as well as Category 6 UTP cables for voice or ISDN low-voltage (digital, 75V) applications.	110 Punchdown

Can also be used for end-span POE applications where power and data are on the all 4-pairs.