

Sold by:



## KRONE® Series 2 K110 25-/50-Pair 89D-Style Blocks



KRONE Series 2 K110 25- and 50-Pair 89D-Style Blocks are now compatible with the industry standard 110 Blade\*. All KRONE pre-terminated products that utilize either the 25- or 50-Pair Series 2 89D-Style Blocks will be transitioned over to the new K110 design.



Easily identifiable with K110  
logo on connector block

### Features and Benefits:

- Wires can be terminated with KRONE Insertion Tool or Industry Standard 110 Blade\*
- New labeling makes pairs and circuits easier to identify
- Patented 45° angled silver-plated IDC technology
- Disconnect Port (integrated bridging clips) allows for circuit monitoring without removal of cross-connect wire—double the density of a 66 block
- IDC Contact accepts 20-26 AWG solid or stranded wire
- IDC Contact accepts 2 conductors of same gauge per contact (22-26 AWG)
- Secure, reliable termination
- Fits on industry standard 89D Mounting Brackets
- Guaranteed greater than 200 reterminations\*
- New contact spacing supports 4-pair wiring without the need to skip every 5th pair
- Can be upgraded with primary and secondary overvoltage protection
- Pre-terminated blocks available with many connector styles and positioning options
- Meets Category 5 specifications in a channel.

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891

# Specifications



<b>Contact resistance:</b>	≤ 1 mΩ
<b>Insulation resistance:</b>	≥ 5 x 10 <sup>4</sup> MΩ
<b>Contact material:</b>	Copper Alloy
<b>Contact plating:</b>	Silver
<b>Transmission performance:</b>	≥ TIA 568B Category 5
<b>Number of test cord insertions:</b>	≥ 750
<b>IDC reterminations</b>	≥ 200
<b>Wire diameter range for solid and stranded copper conductors:</b>	
<b>Two conductors per contact (same diameter):</b>	22-26 AWG (0.65 to 0.40 mm)
<b>One conductor per contact:</b>	20-26 AWG (0.90 to 0.40 mm)
<b>Wire insulation diameter range (PE, PVC):</b>	0.027" to 0.063" (1.60 to 0.68 mm)
<b>Safety rating:</b>	UL1863
<b>Flammability rating:</b>	UL 94 V-0
<b>Telcordia Technical Reference:</b>	TR-NWT-001195
<b>Dimensions: (25- and 50-Pairs)</b>	10" H x 3 3/8" W x 1 3/8" D (254.0mm H x 85.7mm W x 34.9mm D)

## Ordering Information

Description	Catalog Number
Series 2 K110 25-Pair 89D-Style Disconnect Block	6639 1 003-01
Series 2 K110 50-Pair 89D-Style Disconnect Block	6652 1 880-10
KRONE Insertion Tool	6417 2 055-01
Series 2 K110 50-Pair Identification Label	6639 3 017-11
Orange Dust Cover, Hinged	6639 2 004-00
Dust Cover, Clear	6586 3 004-00
89D Bracket for 25- and 50-Pair Disconnect Blocks	6639 3 016-00
Series 2 Bridging Test Cord – One pair with two banana plugs	6646 2 900-XX <sup>+</sup>
Series 2 "Look-Both-Ways" Test Cord – One pair with four banana plugs	6647 2 900-XX <sup>+</sup>
Series 2 "Look-Both-Ways" Test Cord – One pair with four alligator clips	6647 2 906-XX <sup>+</sup>
Series 2 One-Pair Site-Mounted Test Cord	6645 2 125-XX <sup>+</sup>
Winged Test Adapter	6646 2 928-00

<sup>+</sup>Substitute XX in part number for desired cord length in feet (01 = 1 ft.; 04 = 4 ft.; 07 = 7 ft.; 10 = 10 ft.)

\*Note: The new Series 2 K110 25-/50-Pair Block is guaranteed for greater than 200 re-terminations using either the KRONE Insertion Tool (6417 2 055-01) or industry standard 110 Blade. When the cut side of the 110 Blade is used, up to 10 re-terminations are possible when cutting the wire. After 10 re-terminations with the cut side of the 110 Blade, the contact can still accept greater than 190 re-terminations, using the KRONE Insertion Tool or 110 Blade with wire snips or other cutting device.

SPEC SHEET



### Web Site: [www.adc.com](http://www.adc.com)

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080  
 Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our web site.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101  
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. KRONE is a registered trademark of ADC. An Equal Opportunity Employer.

1303455 8/05 Original © 2004, 2005 ADC Telecommunications, Inc. All Rights Reserved