

16893




Description

20-Amp, 120-Volt, Compact Automatic Reset Right Angle GFCI, grounded, accomodates UL / CSA cord types SJTW, SJTOOW, SJTOW, SJEOW, RoHS compliant. BLACK

Product Features

- Grounding: GFCI Ground Fault
- Feature: Power Indication
- Cord Range: .300 - .450
- Voltage: 120 Volt
- Amperage: 20 Amp
- UL 943: Class A (GFCI)
- Pole: 2
- NEMA: 5-20P
- Wire: 3
- Color: Black

Color: Black



NEMA: 5-20P



Features and Benefits

- Rainproof, Outdoor rated GFCI Module.
- Fully complies with NEC and OSHA regulations for construction sites.
- Automatically resets to ON when plugged in or after power interruption.
- Power Indicator lamp goes OFF if GFCI trips, power is interrupted or the GFCI is unplugged.
- Open-Neutral Protection immediately trips the GFCI if the neutral conductor on the line side is opened, eliminating the possibility of the GFCI having a live hot leg.
- Specially designed NEMA 3R, Raintight-While-in-Use cover available.
- UL listed; complies with UL Standard 943 as a Class A GFCI power supply.
- CSA Certified.



AC Horsepower Ratings	
At Rated Voltage	3/4 Horsepower
Environmental Specifications	
Flammability	Rated V-2 per UL94
Operating Temperature	-35C - 66C
Mechanical Specifications	
Product ID	Ratings permanently marked on device

Electrical Specifications	
Current Interrupting	2 kA
Trip Level	5mA plus or minus 1mA
Material Specifications	
Body Material	Polycarbonate
Blades/Contacts	Brass
Standards and Certifications	
NEMA	WD-6
ANSI	C-73
CSA Standard	C22.2 No 144
NOM	057

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 ·

www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2007-2009 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

