

▲ **Products**



K-6000-DVA

Compatible Products: None

Automated Voice Message Delivery System

Model K-6000-DVA can automatically notify up to 1000 people of an event or an event cancellation, school or business closing or delayed opening. The K-6000-DVA is designed to connect to a standard analog CO line, PABX station or VoIP ATA or FXS port. To activate the unit, an authorized official calls the K-6000-DVA, dials a 6 digit access code, selects a pre-recorded message or records a live message up to 1 minute, then activates the unit via a touch tone command to automatically call all the phone numbers in a pre-programmed group. Up to 6 groups of phone numbers can be pre-programmed into the unit. Alternatively, activating an "All Call" command calls all pre-programmed numbers. The K-6000-DVA can also be activated (or cancelled) by up to 8 external momentary push buttons (not included). In the event any called number is busy or doesn't answer, the unit will retry the unanswered numbers several times (programmable 1-9) after all other numbers are called. The maximum number of rings before calling the next number is programmable 1-8 rings (6-48 seconds). The unit waits 2 seconds for touch tones after the message is delivered, if a * is detected, the message is replayed once. For critical applications, the K-6000-DVA can be programmed to require a positive confirmation - the called party must send a pre-determined touch tone to confirm that the message was received. The K-6000-DVA can be programmed from your PC's USB or RS-232 port.

Applications

- Schools
- Churches
- Businesses
- Government / community
- Civic organizations
- Apartment/office information and notification, ie: snow removal, carpet cleaning, etc.

Features

- Non-volatile memory (no batteries required)
- Stores up to 1000 14-digit numbers
- Up to 6 groups
- 8 minutes of total record time total
- Eight normally open inputs for push buttons to activate groups 1-6, "All Call" or "Stop"
- Programmable ring delay for remote programming
- Call progress detection determines when answered
- Programmable ringback limit for call progress (1-8)
- Programmable "retry" limit (1-9) for calls that are busy or don't answer
- Remote security and access codes
- Local or remote programming and recording
- Program from your PC's USB or RS-232 port (RS-232 to USB adapter included)
- Up to 8 K-6000-DVAs can be connected to 1 PC
- Master/Slave mode for multiple levels of K-6000-DVAs
- Compatible with the RC-2A and RC-3 remote DTMF controllers
- Line level input for loading pre-recorded messages into the unit
- Activity reports available

Specifications

- Power: 120V AC/12V DC 500 mA, UL listed adapter provided
- Dimensions: 211mm x 160mm x 46mm (8.3" x 6.3" x 1.8")
- Shipping Weight: 1.02 Kg (2.25 lbs)
- Environmental: 0°C to 32°C (32°F to 90°F) with 5% to 95% noncondensing humidity
- Talk Battery: 12V DC
- Touch Tone Dialing: 120 ms on/off, 50 ms on/off
- CPC Detection Time: 320 ms minimum
- Message Record Time: 8 minutes
- Sampling Rate: 64 K (equivalent)
- Input Detection Time: 80 ms
- Connections: (1) RJ11 jack for telco connection, (2) 3.5mm jacks for 600-ohm audio output and record in, (1) 9 pin RS-232 for PC connection, (1) 12 position screw terminal block for inputs

Information... (715) 386-8861
info@vikingelectronics.com

Fax Back System... (715) 386-4345
[Click here for International Sales](#)

