

Fire-Rated Poke-Throughs Pedestal Series – Painted Aluminum

ScrubShield™
Complies with UL514A



2 Inch Through-Floor Fitting

Description	Catalog Number
Through-floor fitting to be installed in a 2" (50.8) diameter hole. Contains 3/4" EMT tube for low-voltage cabling and 1/2" EMT tube for power wiring for use with Hubbell FR280, FR480 and FR680 series pedestals. This unit will accommodate floor thicknesses of 2 1/4" to 7 inches (57.2 to 177.8).	PT27A

Note: Hubbell PT27A through-floor fitting is approved for use in the city of Chicago.



PT27A

3 Inch Through-Floor Fitting

Description	Catalog Number
Through-floor fitting to be installed in a 3" (76.2) diameter hole. Contains 1 1/4" EMT tube for low-voltage cabling and 1/2" EMT tube for power wiring for use with Hubbell FR480 and FR680 series pedestals (not for two-gang FR280 pedestals.) This unit accommodate floor thicknesses of 2 1/4" to 7 inches (57.2 to 177.8).	PT7XC

Note: Hubbell PT27A through-floor fitting is approved for use in the city of Chicago.



PT7XC

Extension Kit

Description	Catalog Number
Used to extend the floor thickness range of the Hubbell PT7XC through-floor fitting when concrete floor thickness range is between 7 and 13 inches (177.8 to 330.2). Kit includes 1/2" x 6" long EMT tube, 1 1/4" long EMT tube, 1/2" EMT coupling and 1 1/4" EMT coupling.	EXT13



EXT13



Dimensions in Inches (mm)