



PT2X2GY -- 2x2 Flush FRPT



PT2X2GY

One-piece 2X2 Flush fire-rated poke-through, Gray.

Product Specifications

Product Type	 2 x 2 Flush
2X2 Flush Offering	One-Piece Units
Color	 Gray
Complies with:	UL 514A requirements for scrub water protection.
Fire Rating	For use in 1, 1 1/2, 2, 3 or 4 hour rated unprotected reinforced concrete floors or in 1, 2 or 3 hour rated floors employing steel floor units and concrete topping (D900 series design).
Floor Thickness Range	2 1/4" (over metal deck) to 7" (57.2 to 117.8)
UL Installation Spacing	Minimum of 2 feet on centers and not more than one unit per 65 sq. ft. of floor area in each span.
Cored Hole	3" (76.2) diameter
Receptacles	Hubbell #HBL2162BK Black, NEMA 5-20R; 20A, 125V AC
Jack(s)	Hubbell HBL5EBK Black; Category 5e; UL Listed; 110 type contacts
Power Conductors	#12 AWG THHN stranded copper.
Device and Cover Flap Material	Thermoplastic
Carpet Flange Material	Painted Cast Aluminum/Solid Brass, Brushed and Laquered.
Conduit Tubes	Power - 3/4" EMT/Low Voltage - 1/2" EMT (two)
Listings	Outlet Box- E31999, Fire Resistance- R8429
Plenum Rating	Acceptable for use in environment air handling spaces per NEC article 300.22(C).
M Drawings	Click here for M-Drawing
Catalog Page	Click here for catalog page M7
Hubbellnet	Click here for Hubbellnet
Catalog Section	Click here for Section-M

UPC Number 78358553186

Weight in LBs 4.2

