

Sold by:



TWAcmm.com
<http://www.TWAcmm.com>
Toll Free: (877) 389-0000

Suppose you would never forget anything



Recall every word, any time

The Call Recorder SD2750 is a true digital recorder easily connected to Up0 and S0 lines. The advantage of connecting between the actual digital line and the telephones, is the reliability, extra information like Caller-ID and flexibility in positioning the machine.

All telephone calls can be automatically stored on the internal solid state Flash memory that will hold over 2.500 hours of recorded calls. In addition the SD2750 has a removable SD-card for quick copying of one or more recordings. The LAN connection provides easy access to the unit for back-up or archiving purposes, with optional PC software.

After being recorded, telephone calls can be played back by the SD2750 itself using the internal speakers or the calls can be copied to a PC for playback. Calls can easily be found by using search criteria like telephone number, caller-id, date, time or duration. Software to access the calls on the SD card is provided with the Call Recorder. For security or privacy reasons the recorded calls are guarded against unauthorised playback, or copying by password protection. If security needs to be even better, the unit can work with the Triple DES encryption technology provided through the optional CryptoCard.

The Call Recorder SD2750 is the ideal single channel solution for demanding recording applications on PBX systems like Siemens, Avaya, Philips or other systems using Up0 or ISDN S0 line technology.



Grey Line Call Recorder Single Digital



vidicode

Specifications

Grey Line Call Recorder Single Digital



Features

- 16 GB internal flash disk
- Removable SD card
- Network connection
- Internal speaker
- Included Quick SD Access software
- Optional encryption

• **Article number: 010.01630**

Technical specifications

- Power: 90-264V ~ 50/60Hz
- Ambient temperature: 0 - 40 °C
- Size: 26 x 19 x 5,5 cm
- Weight: 1000 grams
- Recording formats:
 - GSM 6.10 - 13kbps
 - G.711

Connections

- Power: 10V DC
- Telecom: 2 x RJ45 (in-out) for UP0 and S0
- Headset: 2 x 3,5mm Jack
- Ethernet: 10-BASE-T / 100-BASE-T RJ45 UTP
- Serial: MiniDIN 8P Female RS232
- Switch: 3,5mm mini-jack / 8 p miniDIN
- CryptoCard reader (front)

Technical approvals

- CE: 55022/55024
- Safety: EN 609050

Software

- Windows™, XP, Vista, Windows 7

Guarantee

- 2 years

Application

Recording to make sure there can be no doubt about verbal agreements. Provide security for public offices (theaters, hospitals etc), any commercial organisation. Use for evaluation and training.




Software

Quick SD Access software to quickly archive one or more recordings on the SD card
Optional Call Recorder Access software
Optional Araña web interface



CryptoCard (optional)

Encryption saves recordings from unauthorised playback or tampering. Only the right CryptoCard and PIN code will make recordings accessible again.



Box content

- Single digital SD2750
- ISDN Cable 2m
- Telephone cable 3m
- Application CD, manual on application CD
- Quick Guide
- SD Card
- Power supply
- Mains cable

vidicode partner:



vidicode

www.vidicode.com