

Twist-Lock® Devices

Accessories

for 15 Ampere 2 and 3 Wire Duplex, Single Receptacles and Flanged Devices



NP8I

NP7I

Single-Gang Wall Plate

Description	Duplex Plate	Single Rec. Plate 1.406" (35.7) Dia.
Brown nylon, smooth.	NP8	NP7
Ivory nylon, smooth.	NP8I	NP7I
Stainless steel 302/304, smooth.	SS8	SS7
Brass, smooth.	SB8	SB7
Aluminum, smooth.	SA8	SA7



HBL5206WO



HBL5221



HBL7423WO



WP1

Weatherproof Plates**IP44**
SUITABILITY

Description	Catalog Numbers	
Cast aluminum, for standard horizontal box mount.	HBL5205WO	-
Same as above except FS/FD box mount.	HBL5206WO	-
Cast aluminum vertical FS/FD box mount.	-	HBL7420
Gray thermoplastic, vertical standard box mount, corrosion resistant.	HBL5222*	-
Same as above except yellow.	HBL52CM22*	-
Gray thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL5221*	HBL7423WO
Yellow thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21*	HBL74CM23WO
White thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21W*	-

**Weatherproof Plate for
15A Flanged Inlets and Receptacles****IP44**
SUITABILITY

Description	Catalog Numbers
Gray thermoplastic, corrosion resistant.	WP1

Notes: All weatherproof plates listed above are UL Listed for wet and damp locations with cover closed. Those with suffix WO are UL Listed with cover open.
See section K for more information.

* IP20 Suitability only.

Straight Blade Devices

Accessories

For 15 and 20 Ampere, 125 and 250 Volts and 277 Volts AC Devices



NP8I



NP7

SS7



HBL52CM22



HBL5206WO



HBL7423WO

**Wallplates, 1-Gang**

Description	Color	Duplex Receptacles	Style Line® Receptacles	Single Receptacles with Face Dia. 1.39 in. (35.3)
Smooth nylon.	Almond	–	NP26AL	–
	Black	NP8BK	NP26BK	NP7BK
	Brown	NP8	NP26	NP7
	Gray	NP8GY	NP26GY	NP7GY
	Ivory	NP8I	NP26I	NP7I
	Light Almond	–	NP26LA	–
	Office White	NP8OW	NP26OW	NP7OW
	Orange	NP8OR	–	–
	Red	NP8R	NP26R	NP7R
	White	NP8W	NP26W	NP7W
	Stainless steel 302/304 satin, smooth, 1-gang.		SS8	SS26
Brass .040 in. (1.02) smooth, 1-gang		SB8	SB26	SB7
Aluminum, anodized, smooth.		SA8	–	SA7

Weatherproof Covers

Description	Duplex Receptacles	Single Receptacles with Face Dia. 1.39 in. (35.3)
RTP, gray, for FS/FD box mounting.	HBL5221	HBL7423WO
RTP, yellow, for FS/FD box mounting.	HBL52CM21	HBL74CM23WO
RTP, gray, for device mounting.	HBL5222	–
RTP, yellow, for device mounting.	HBL52CM22	–
Cast aluminum for FS/FD box mounting.	HBL5206WO	HBL7420
Cast aluminum for device mounting.	HBL5205WO	–

Notes: All weatherproof plates are UL Listed for Wet Locations. Those with suffix WO are listed for use with cover open, all others with cover closed. Refer to Section K for more details on cover plates. RTP is an abbreviation for reinforced thermoplastic polyester.

