**Overview** 

## **PANDUCT® Notching Tool**



· Notches duct sidewalls to bottom scoreline for tee and corner junctions

Part Number	Part Description	Std. Pkg. Qty.
DNT-100	Hand held sidewall notching tool.	1

Always use approved safety goggles when using any tools.



Notch wiring duct sidewall at the desired opening width.



Step 2 — Snap off notched wiring duct piece at bottom scoreline.

## PANDUCT® Nylon Rivet Installation Tool



• Installs PANDUIT® Nylon Rivets (NR1) quickly and easily

Part Number	Part Description	Std. Pkg. Qty.
TNR	Hand held nylon rivet installation tool.	1

**Nylon Rivets** 

ln.

.158 - .187

.188 - .218

.219 - .250

.251 and up

NR1-C	Nylon rivet for use with TNR Rivet Tool.	100
NR1-M	Nylon rivet for use with TNR Rivet Tool.	1000

ln.

.18

.19

.20

.21

**Panel Hole** 

Dia. Needed

mm

4.7

4.9

5.2

5.4

Always use approved safety goggles when using any tools.

mm

4.0 - 4.7

4.8 - 5.5

5.6 - 6.4

6.5 and up

**Total Thickness of** 

**Panel and Duct** 

Γ	N	R



NR1

- Fast, lowest cost mounting method
- · Installs quickly and easily using PANDUIT® Rivet Installation Tool (TNR)

TWAcommocom http://www.TWAcomm.com Toll Free: (877) 389-0000



Step 1 — Insert rivet in tool.



Step 2 — Position rivet into hole.



Install rivet with sharp tap.

Control Panel

Special Environment

> Voice & Data

Tools & Accessories

Technical Info

Index

