

Ortronics

OR-60950090

Series II, two-port (1 RJ25C, 1 Category 5e T568B), 180° - OR-60950090

Series II, two-port (1 RJ25C, 1 Category 5e T568B), 180°

**FEATURES**

- Linear 110 paired punch down
- Front removable
- Rugged snap-in design
- Icon compatible

BENEFITS

- Faster than other termination methods
- Less intrusive access for adds, moves, changes
- Quick and easy
- Supports TIA/EIA 606 standard

Specifications

© 2009 legrand

Sold by:



CONSTRUCTION INFO

Component4: Printed circuit board
Material3: Phosphor bronze
Finish Plating3: Nickel plating and tin lead over plate
Material2: Phosphor bronze
Component1: Plastic Series II Housing
Component2: One array of six linear modular contacts and one array of eight linear modular contacts
Material1: High Impact Thermoplastic ABS 94V-0
Component3: IDC contacts, 110 D4
Material4: Two-sided FR-4 epoxy resin/glass base with solder mask
Finish Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

DIMENSION INFO

Width U S: 1.89"
Width Combined: 1.89" (48.01 mm)
Height Combined: .92" (23.37 mm)
Height Metric: 23.37 mm
Width Metric: 48.01 mm
Height U S: .92"

GENERAL INFO

Category Performance Application:	Category 5e/UTP
Product Type Accessory:	Modular Jack
Number Of Ports:	2-port
Critical Size:	1 unit
Product Type Accessory For Filter:	Modular Jack
Color Filter:	Fog White
Footprint:	Series II

TECHNICAL INFO

Wire Gauge: 22-26 AWG
Category Rating: Category 5e